

MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS:1963 A

*, DR 1340 May 84

AD-A143 549

METEUROLOGICAL DATA REPOR!

14823B Lance
Missile Number 5342
Round Number 397-AST
12 April 1984

bу

DONALD C. KELLER
Program Support Coordinator
Phone Number (505) 679-9568
AVN Number 349-9568

ATMOSPHERIC SCIENCES LABORATORY WHITE SANDS MISSILE RANGE, NEW MEXICO

ECOM
UNITED STATES ARMY ELECTRONICS COMMAND

84 07 24 017

DISPOSITION INSTRUCTIONS

Destroy this report when it is no longer needed. Do not return to the originator.

DISCLAIMER

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The citation of trade names and names of manufacture's in this report is not to be construed as official Government indorsement or approval of commercial products or services referenced herein.

SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

REPORT DOCUMENTATION	ON PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
DR 1340	AD-2143 547	
. TITLE (and Subitite)	,	5 TYPE OF REPORT & PERIOD COVERED
14823B Lance		
Missile Number 5342 Round Number 397-AST		6. PERFORMING ORG. REPORT NUMBER
Round Number 397-AS1		
7. AUTHOR(e)		8. CONTRACT OR GRANT NUMBER(a)
Hinite Sands Meteorological Team		DA Task 1F665702D127-02
PERFORMING ORGANIZATION NAME AND ADDR	ESS	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
1 CONTROLLING OFFICE NAME AND ADDRESS		12. REPORT DATE
US Army Electronics Research & De	evelopment Cmd	12 Apr 84
Atmospheric Sciences Laboratory White Sands Missile Range, New M	exico 88002	13. NUMBER OF PAGES
White Sands Missile Range, New Move MonitoRing Agency Name & Address(it dite		15. SECURITY CLASS. (of this report)
US Army Electronics Research and	Development Cmd	1990 4007755
Adelphi, MD 20783		UNCLASSIFIED
		150. DECLASSIFICATION/DOWNGRADING
6. DISTRIBUTION STATEMENT (of this Report)		SCHEDULE
6. DISTRIBUTION STATEMENT (of this Report)	ered in Block 20, if different fro	SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) 17. DISTRIBUTION STATEMENT (of the abetract enter		SCHEDULE Per Report)
6. DISTRIBUTION STATEMENT (of this Report) 17. DISTRIBUTION STATEMENT (of the abetract enter		SCHEDULE Per Report)
6. DISTRIBUTION STATEMENT (of the Report) 17. DISTRIBUTION STATEMENT (of the abetract enter Approved for public release; dis		SCHEDULE Per Report)
6. DISTRIBUTION STATEMENT (of the Report) 17. DISTRIBUTION STATEMENT (of the abetract enter Approved for public release; dis		SCHEDULE Per Report)
6. DISTRIBUTION STATEMENT (of the Report) 17. DISTRIBUTION STATEMENT (of the abetract enter Approved for public release; dis	tribution unlimited	SCHEDULE Man Report)
17. DISTRIBUTION STATEMENT (of the abetract enter Approved for public release; distances of the supplementary notes	tribution unlimited	SCHEDULE Man Report)
17. DISTRIBUTION STATEMENT (of the abetract enter Approved for public release; distances of the supplementary notes	tribution unlimited	SCHEDULE Man Report)
Approved for public release; dis	tribution unlimited	SCHEDULE Man Report)
17. DISTRIBUTION STATEMENT (of the abetract enter Approved for public release; distances of the supplementary notes	tribution unlimited	SCHEDULE Man Report)
15. DISTRIBUTION STATEMENT (of the abstract enter Approved for public release; dis- 16. SUPPLEMENTARY NOTES 18. KEY WORDS (Continue on reverse side if necessaria)	tribution unlimited ry and identify by block number, y and identify by block number,	SCHEDULE Sen Report)
15. DISTRIBUTION STATEMENT (of the abstract enter Approved for public release; distinct supplementary notes 16. Supplementary notes 16. KEY WORDS (Continue on reverse side if necessary meteorological data gathered for	tribution unlimited by and identify by block number, and identify by block number) the launching of i	the 14323B Lance, Missile
15. DISTRIBUTION STATEMENT (of the abstract enter Approved for public release; dis: 16. SUPPLEMENTARY NOTES 18. KEY WORDS (Continue on reverse elde II necessar	tribution unlimited by and identify by block number, and identify by block number) the launching of i	the 14323B Lance, Missile
15. DISTRIBUTION STATEMENT (of the abstract enter Approved for public release; distinct supplementary notes 16. Supplementary notes 16. KEY WORDS (Continue on reverse side if necessary meteorological data gathered for	tribution unlimited by and identify by block number, and identify by block number) the launching of i	the 14323B Lance, Missile
15. DISTRIBUTION STATEMENT (of the abstract enter Approved for public release; dis: 16. SUPPLEMENTARY NOTES 16. KEY WORDS (Continue on reverse side if necessar Meteorological data gathered for	tribution unlimited by and identify by block number, and identify by block number) the launching of i	the 14323B Lance, Missile
6. DISTRIBUTION STATEMENT (of the abstract enter Approved for public release; distant supplementary notes 9. KEY WORDS (Continue on reverse side if necessary Meteorological data gathered for	tribution unlimited by and identify by block number, and identify by block number) the launching of i	the 14323B Lance, Missile

	CONTENTS	PAGE
INTRODU	CTION	1
DISCUSS	[ON	1
GENERAL	AREA MAP	2
TABLES:		
1.	Surface Observation Taken at 0525 MST at LC-39	3
2.	LC-36 Pilot-Balloon Measured Wind Data Taken at 0515 MST	4
3.	LC-36 Pilot-Balloon Measured Wind Data Taken at 0532 MST	5
4.	Aiming and T-Time Computer Met Message Data	6
5.	WSD Significant Level Data at 0001 MST	7
6.	WSD Upper Air Data at 0001 MST	8
7.	WSD Mandatory Levels at 0001 MST	13
8.	NW-30 Significant Level Data at 0230 MST	14
9.	NW-30 Upper Air Data at 0230 MST	15
10.	NW-30 Mandatory Levels at 0230 MST	19
11.	Jallen Significant Level Data at 0400 MST	20
12.	Jallen Upper Air Data at 0400 MST	22
13.	Jallen Mandatory Levels at 0400 MST	27
14.	WSD Significant Level Data at 0525 MST	28
15.	WSD Upper Air Data at 0525 MST	29
16.	WSD Mandatory Level Data at 0525 MST	34

INTRODUCTION

14823B LANCE, Missile Number 5342, Round Number 397-AST, was launched from LC-39, White Sands Missile Range (WSMR), New Mexico, at 0525:03 MST, 12 Apr 1984. The scheduled launch time was 0400 MST.

DISCUSSION

Meteorological data were recorded and reduced by the White Sands Meteorological Team, Atmospheric Sciences Laboratory (ASL), White Sands Missile Range, New Mexico. The data were obtained by the following methods:

- 1. Observations
 - a. Surface
- (1) Standard surface observations to include pressure, temperature (°C), relative humidity, dew point (°C), density (gm/m^3) , wind direction and speed and cloud cover were made at the LC-39 Met Site at T-0 minutes.
- (2) Monitor of wind speed and direction from one anemometer was provided in the launch control room.
 - b. Upper Air
- (1) Low level wind data were obtained from RAPTS T-9 pibal observation at:

SITE AND ALTITUDE

LC-36 7,000 ft. LC-36 10,000 ft.

(2) Air structure data (rawinsonde) were collected at the following Met Sites.


SITE AND TIME

WSD 0001 MST NW-30 0230 MST JAL 0400 MST WSD 0525



AT

WSMR METEOROLOGICAL SITES



PROJECT SURFACE OBSERVATION

TABLE	1							STATIC'I LC-39	-39		
DATE 12	Apr	84	ا					X= 530,938.82	2 Y= 1.	Y= 136,564.96 H= 4,063.75	4,063.75
TINE MST	PRESSUPE mbs	'	PATURE OC	300 300 300 300 300 300 300 300 300 300	POINT	PELATIVE HUMIDITY	E::11Y g::/m3	DIRECTION SPEED degs In kts	WIND SPEED Kts	CHARACTER kts	VISIBIL- ITY
0525	876.2		8.2		9.6-	27 ·		020	04		30
						,					

	RE: A PKS			
	ď	НСТ		
	d LAYE	A:T TYPE HGT		
	350	A:11		
	Ď	HST	26000	
CI DIEDS	2nd LAYER	TYPE	Ci	
	l 2no	AM		
	ď	HGT	14000	
	t LAYE	AMT TYPE HGT	0 A C	
	15	AMT	0	
		TO VISIBILITY		

PSYCHROMETRIC COMPUTATION

TITE: MST	0525	
DRY GULB TET:P.	8.2	
WET BULB TEMP.	1.4	
WET BULB DEPR.	6.8	
DEW POINT	9.6-	
RELATIVE HUMID.	27	

WINDS ALOFT DATA

TABLE NUMBER2					
RELEASED FROM LC-36	DATE	12 Apr 84	TIME 0515	TOT XXX TOT	
WSTM COORDINATES: X= 504,4	67.18	Y= 190,776	.98 ·:=_	4,040.71	
"ETHOD OF DATA COLLECTION:	`s/T	D/T	1- 9 x	RADERAWIN	
METCHTS - METERS AGI - F	FFT AGI X	VETEDS HOL	FEET I'SI		

HEIGHT	DIRECTION DEGREES	SPEED KTS
SFC	355	08
200	285	10
400	346	19
600	352	29
800	359	30
1000	003	28
1200	004	27
1400	008	26
1600	015	24
1800	018	23
2000	022	22
2200	018	21
2400	024	18
2600	025	17
2800	031	16
3000	023	10
3200	025	08
3400	012	08
3600	349	06
3800	355	05
4000	320	07
4200	319	07
4400	330	08
4600	314	12
4800	315	12
5000	311	17
5200	304	16
5400	292	18

	DIRECTION	SPEED
HEIGHT	DEGREES	I:IS
5600	287	19
5800	285	20
6000	294	23
6200	292	23
6400	284	24
6600	284	28
6800	282	33
7000	277	32
ļ		

	DIRECTION	SPEED
HEIGHT	DECPEES	ــــــــــــــــــــــــــــــــــــــ
		
		
		ļ
		
		
		
		
		
		
-		
	· · · · · · · · · · · · · · · · · · ·	
		
		<u> </u>
		
		
		L

WINDS ALOFT DATA

TABLE NUMB	ER	_						
RELEASED F	ROM LC-36	DATE	12 Apr 84	TIME	0532	:ST_X		
USTM COORD	INATES: X= 504	,467.18	Y= 190,776.	.93	1]=	4,040.71		_
ETHOD OF	DATA COLLECTION	: `S/T	D/T		Х	PAOS	PANIN_	_
HETCHTS.	METERS AGE	FFFT AGL X	WETERS HSI	FFF7 '	12			

	DIRECTION	SPEED
HEIGHT	DEGREES	KIS
SFC	345	07
200	М	M
400	351	08
600	345	25
800	357	27
1000	003	28
1200	007	26
1400	007	25
1600	004	23
1800	006	22
2000	013	21
2200	022	21
2400	023	15
2600	033	15
2800	033	13
3000	025	10
3200	022	08
3400	023	07
3600	025	07
3800	006	07
4000	343	05
2400	322	05
4400	320	07
4600	315	08
4800	319	08
5000	315	09
5200	304	11
5400	301	14

	DIRECTION	SPEED
HEIGHT	DEGREES	KIS
5600	301	15
5800	290	17
6000	284	20
6200	280	27
6400	280	28
6600	279	25
6800	282	27
7000	284	28
7200	281	30
7400	276	31
7600	275	32
7300	273	31
8000	271	31
3200	271	31
8400	271	29
8600	274	29
8800	275	29
9000	280	26
9200	280	25
9400	283	24
9600	286	23
9800	291	23
10000	293	23
	, <u></u>	
	,	
]		Į į

UE I CUT	DIRECTION DESPEES	SEEE
HEICHI	TIF CALLED	1.73
···		
- 		
· 		
		
		

AIMING AND T-TIME COMPUTER MET MESSAGE DATA

12 April 1984

WSD 0001	MST	NW-30 023	0 MST	JALLEN 04	00 MST	WSD 0525	MST
METCM1324	064	METCM1329	065	METCM1332	065	METCM1324	064
120700122	875	120950122	876	121100124	874	121240122	878
00640010	28990875	00000000	28540876	00444004	28570874	00053010	28590878
01011020	29090864	01101007	28690865	01543008	28620864	01013023	28580867
02006023	29000839	02041012	28600840	02464004	28640838	02023025	28550842
03599015	28720801	03020010	28380801	03530021	28260799	03024008	28450802
04545016	28380754	04590007	28120754	04583017	28120752	04598008	28190755
05499022	28060710	05533021	27890709	05541020	27880708	05516016	27870711
06482025	27800668	06499025	27620667	06483026	27510666	06492025	2 7 560568
07502028	27450628	07514027	27240627	07492023	27150625	07502022	27250628
08501035	27040590	08509035	26850589	08500029	26780587	08501024	26870590
09501038	26640554	09489037	26470552	09498038	26410551	09492031	26490553
10498042	26240519	10494040	26090518	10501043	26040516	10497034	26080519
11489040	25880486	11497041	25780485	11497045	25720483	11509036	25710486
12465035	25400440	12487041	25290438	12500046	25190437	12509039	25230439
13464035	24740384	13484044	24530382	13492051	24440381	13497037	24470383
14487033	23840334	14467044	23710332	14479056	23690331	14480039	23720332
15497036	22950289	15485046	22840287	15478055	22800286	15490042	22860287
16501037	22060248	16492047	21940246	16481052	21910245	16485043	22020247
17494033	21220212	17490045	21110210	17496054	21140209	17486046	21290211
18517044	20660180	18514048	20730179	18512058	20760178	18511047	21020180
19493035	20770153	19501047	20840152	19510065	20970151	19512049	21040153
20499053	20550130	20518051	20650129	20526054	20700129	20543044	20790130
21516054	20600110	21522060	20750109	21528055	20600109	21537035	20740110
22524041	20900093	22538039	21030093	22535033	20840093	22535021	20680094
23484008	21360080	23360005	20910079	23420013	20930079	23502024	20850080
24419008	21070068	24450025	21050067	24491008	21240067	24510017	21320068
25467007	21190058	25443019	214 30 05 7	25620008	21210057	25557017	21470058
26048005	21440049	26076011	21340049	26059009	21510049	26021005	21540049

STATION ALTITUDE 3969.NO FEET MSL 12 AP?. 84 UDO1 HRS MST ASCENSION NO. 206

SIGNIFICANT LEVEL DATA 1030020206 WHITE SANDS

GEODETIC COORDINATES 32.40043 LAT DEG 106.37033 LON DEG

TABLE 5

REL.HUM. Percent	ė	7		5	~	0	30.0	•	30	0																								
FRATURE DEWPOINT CFNTIGRA	•		*	0		17.	-27.0	8	9	5.00																								
TEMPI AIR OFGREFS	•	•	•	•	•	•	2	21.	23.	39.	41.	52.	64.	69	66.	. 49	63.	65.	68.	66.	70.	66.	66.	63.	57.	4	60	51.	57.	8	5.3	-52.9	50.	a
GLOMETRIC ALTITUDE MSF FFFT	989°	187.	784.	453.	0110.	1757.	8873.	2970.	4351.	1169.	1010.	5000	0638.	1984.	2503.	3043	4177.	2400.	5491.	8523.	9940.	1302.	3463.	5745.	8.085	.6720	2714.	5905	7647.	.7.80	9 551.	82927.6	7021.	1.44
PPESSURE	74.	63.	50.	7.	9	58.	°	23.	90	12.	00	50.	9	77.	3.	68	59.	•	2		•	ċ	6	ċ	6	ċ		;	ċ	\$	ċ	24.5	0	` ∢

STATION ALTITUCE 3989.00 FEET MSL 1. APM. 84 0001 HRS MST ASCENSION NO. 206

UPPER AIR DATA

GEODETIC COORDINATES

1. AP P. 8	^	0001 HRS	HST TSE		WHITE SAND	000		32.40	COCKDINA D
S C E N S I O	902 •0				ĹŦ			106.	7033 LON DE
EOME TR	PRESSURE	Ŧ	1	REL.HUM.	NSIT	SPEED OF	IND	ATA	INDEX
ALTITUDE MSL FIET	MILLIBARS	AIP DEGREES	DEWPOINT CENTIGRADE	E RCE	GM/CUBIC METER	SOUND	DIRECTION DEGREES(TN)	SPEED	OF REFRACTION
Ċ	876	•		16.0	50.0	63	9	•	7 0 0
0	874.	9	5	16.1	0	63.	29		77000
ó	858.	17.4	6-2-	17.0	2 A	664.5	52.	8.6	002
.0	843.	0	ຜ	17.2	017.	63	5	0	00024
0	628.	\$	•	17.8	97.	62.	51.		00023
ċ	813.	,	ò	10.4	8 	61.	. 64	7	7000
ċ	798.	÷	•	18.9	69	60.	37.	\$	2000
00	784.	~	•	Ġ	55.	58.	23.	4	00027
0,	770.	:	ر	ځ	5.4	5.7	14.	\$	00022
ģ	756.	10.4	-10.1	5	2 2.	56.	06.	•	00022
.G.	742.		-9.7	\$	14.	55.	.66	7.	00021
0.	729.	80 4	5.4-		00	54.	. 76	•	00021
0	715.	7.4	-9.3	Š	64	53.	9.4.		00021
• 00 DO	792.	•	-6.5	;	74.	51.	77.	2	© 2000
05.00.	689.	•	9.01-	٠ د	ç°	51.	73.	~	07000
از دن	677.	•	-15.1	\$	47.	50.	71.	•	00050
15.00	.,99	•	-15.6	÷	3.	6 9	73.	۶.	00019
2002	652.	3.5		ؿ	21.	6 8 •	76.	÷	00019
, S	6:0	•	-17.9	÷	چ.	46.	φ •	٧.	00014
3017	627.	э. •	- 10.5	÷	46.	45.	81.	œ	00018
35 c5.	615.	۲.	-19.1	?	ε5.	43.	81.	ċ	0001 R
* 000 *	6C3.	:	3.64-	~	7.4	42.	82.	۶.	00017
• Gn 5*	592.	~		÷	د′ ۲	* 0.	82	·	00017
• OF 37	580.	· % -	-21.5	2 4.6	50.	1	∞		2017
٠ ۲	569.	Š		'n	39.	38	82.	÷	00017
60.09 (55°	ò		ċ	, 7	9.	8 2.	۲.	00014
55 U.	548.			ė	α.	2	8-	•	0001¥
<u>,</u> 0′, 0′,	517.	÷	•	۲.	ر. د	3	90.	ċ	00016
75.00.	527.	ċ	•		۰ ۱۰	32.	ະ ພ	ô	20€14
• 0 T 0 P	517.	-	Ü	•	٥٧.	, O .	42.	_:	0.0015
ج در در	507.	12.	•	• حر	77.	29.	• a;	~	0001
0000 0000	407	13.	٠,	.>	• •	28.	50.	٠	0001
ر د د	.83.	- 4 -	æ	ů	56.	56.	2	ċ	00014
້: ປ	.77.	† 5 .	ن	7.	v.	25.	70.		00014
٠٦٠ ح	4 £ 0 •	•	٠	٠,	54.	56.	67	•	00014
100	450.	17.		;	. 7 7	23.	. 79	•	0000
	671	œ (7.7	6.25	7 .	25.	29	٠.	
2	<	3.61	· '	:		•	• (ς.	
	• • • •	3.0.	L • / • -	٠ • •	•	619.7	Λ,	2.65	*. L000 • L
•	· () •			,	9 4	נצ	\sim	٠	د:

STATION ALTITUDE 3959.00 FEET MS. 1. APM. 84 ASCENSION NO.

UPPER AIR DATA 1030020206 WHITE SANDS

GFORETIC CUURDINATES 32.40943 LAT REG 106.37033 LON DEG

1.000129 .00000 1.0000.1 .0000.16 .000119 .000115 .000109 .0001 "6 .000106 .0001 nt .0000 .0000. .000. .0000 .0000. .0000F2 U* 00000. .0001 . 0000 .000113 .000111 .000102 .000101 .00000 .0000 .0000. **~~0000**• \$70000. .n00013 010000 .00000 .0000 . 00017 .000117 .00000 5,0000. .0000. REFRACTION 34.3 37 . R 39 . F SPEED KNOTS WIND DATA DEGREES(TN) DIRECTION 280.7 280.7 781.8 282.4 282.7 282.0 282.0 280.0 278.1 276.1 276.0 279.5 281.9 284.8 292.0 SPEED OF 617.6 616.6 615.5 012.1 610.4 608.7 598.4 594.9 591.2 591.4 589.7 558.0 556.7 559.6 607.0 603.6 601.8 596.7 587.9 584.3 580.8 579.0 577.3 575.6 6.05.3 586.1 KNOTS SOUND TABLE 6 Con't 421.9 414.8 407.9 15 7.6 14 7.3 34 1.0 574.4 564.4 4.352 496.5 488.3 481.7 466.4 458.4 453.8 463.8 429.0 394.5 367.3 380.3 371.4 434.9 300.1 REL-HUM. DENSITY PERCENT GM/CUBIC MF TER 19.6 19.8 19.9 14.0 14.0 222280 16.4 19.4 DEWPOINT DEGREES CENTICRAD 150.8 151.9 158.6 179.4 -47.5 -47.3 -47.3 -45.4 -48.6 -39.4 -41.1 -46.5 TEMPERATURE Al? DEWPOI -21.9 -22.7 -23.6 -35.0 -31.8 -33.1 -45.9 -48.6 6.65-6.99-6.65--34.5 -37.4 1.23--44.1 4.54--46.6 -49.5 -50.9 -52.3 -53.5 -54.8 -56.1 -58.6 -43.7 -65.9 MILLIBARS PRESSURE 255.9 238.3 227.7 227.7 221.7 216.4 206.2 196.4 191.5 182.8 177.7 22.55 22.55 22.55 23.55 34500.0 \$5000.0 5500.0 36000.0 65.00.0 70000 75.0.0 0.00.38 85.0.0 0.00368 GEOME TRIC 13 3 TSW ALTITUDE

-46.8

.0000.

0.0

AT LEAST ONE ASSIMITE RELATIVE HUMITATY VALUE WAS USED IN THE INTERPOLATION

3969.00 FEET "SL	0001 HRS #ST	9
TION ALTITUDE	' &	ENSION NO. 206
T1 0N	APF. 84	ENSI

UPPFR AIR DATA 1030U-22206 White Sands

GEODETIC COORDINATES 32-40043 LAT DEG 106-37033 LON DEG

ASCENSION	NO. 206			TABLE 6 (Con't		106.	\$7033 LON DEG
GLOME IRIC	PRESSURE	TEMPERATURE	E.E.	ENSIT	SPEED OF		1	INDFX
LTITUD		ATO UTWPOTA	CENT	3	SOUND	TRECTION	PFF	3 30
SL F!E	MILLIBARS	DEGREES CENTIGRADE		HETER	KNOTS	DEGREES(TN)	KNOTS	REFRACTION
. 5	• •	m		74.	8	ŏ	0	2
4 000	000	P)		7	' 0	, 60	N 00 00 00 00 00 00 00 00 00 00 00 00 00	5 ×
45.0.	56.	-		61.	63.	. 60		
5000	53.	in		26.	61.	. 89	: _:	Š
55 10.	6 7	7.99-		51.	60.	9		. ~
6 6.29•	45.	~		46.	59.	9	,	0000
65 .n.	41.	an .		41.	57.	73		0000
70.00	ဆို	~		234.8	r.	280•⊓	45.6	
. S.	3.5	7-12-		28.	58.	8		0000
900 S0	31.	99		22.	59.	80	œ	.0000
0. 88	8	7.991		15.	60.	5	•	.000
90 00	25	67.		5	58.	06	- :	.000.
95 cū.	22.	Δ.		08.	56.	8	۶.	0000
	19.	70.		04.	55.	80	•	.0000
65.50	3	68		9.4	57.	87		0000
1000	5	67		91.	59.	87	•	0000
15 (U.	9	ş		6.5	60.	8	;	.0000
20.07 7.00.07	• ¿ o	9		င့်	60.	8	•	0000
. C. C.	•	ç		7 6.	60.	80. N	ċ	.000
	70	Ç		72.	ç,	86	۲,	0000
0.00	• > f	J . 001		67.	9	8	•	•
	٠,	6		•	61.	ص ص	Š	0000
4500.	٠,	4		α.	62.	46	÷	.0000
٠, c.	į	9		4	63.	æ. œ.	,	0000
٠ د د د	•	S,		•	. 49	œ.	٥.	1000
200	Ď,	7		٠.	65.	0	۶.	.0000
· · · · · · · · · · · · · · · · · · ·		5		•	67.	03	,	0000
	•	9			68	2	۲.	0000.
	•	3. 1 3. 1		٠.	70.	<u>د</u>	ċ	0000
	• •	· (•	:	0	•	2000°
• C : (A)	2) ,	~ ^		ť	.0	67	۲.	-00000
	•	S		;	69	5	•	, 0000
	•	7		۶.	67.	4		<u>. 0000 .</u>
		\sim		•	55.	Š	•	20000
် (၂)	، د	63		۴.	64.	\sim	•	0000
	•	•		٠.	63.	5	•	0000
ر د د	•	Ş-			54.	0		\mathcal{L}
	•	2		·	.0	25	•	ევდის
6.55 (3.00)	9.49	-61.5		10°.5	567.1	147.	\$ • a	1.000374
	•	5		102.9	57.	F .	•	_

UPPER AIR DATA

TABLE Cont FRESLURE TEMPRETURE REL-NUM DEFIET SPEED TABLE Cont TABLE	TATIONA	LTITUDE 39	39.00 FEET		10300202	A 1 4 0 0 6		GEODETI	C COORDINATE
TABLE 6 CON'T. If RIT PRESSURE TEMPERATURE RELHUM, DENSITY SPEED OF DIRECTION SPEED OF D	Z APR. 8) 	0001 HRS MST		WHITE SAN	DS		32.	40043 LAT DE
TABLE CON'T. TIUDE A 10 OFFICIAL SPEED OF RECTION SPEED OF RECTION SPEED OF STATE OF SPEED OF STATE OF SPEED	SCENSIO	0. 20						90	37 033 LON DE
First Pressure Personal Religion Persona					9	Con't			
March Marc	HE TRI	RESSU	TEMPERAT	EL.HUM	EMS1T	PEED O	OUNIA	TA	NOF
10000 100000 100000 100000 100000 100000 100000 100000 10000	9 U.	ILLIBAR	DEGREES CENTIGRAD		METER	KNOTS	EGREESCTN	NON	EF RACT 10
100002 111.0 111	35.30.		-61.1		00	67.	26		0000
\$5.0.0 \$6.0 \$18.7 \$1.5 \$10000 \$5.0.0 \$6.0 \$1.5 \$6.0 \$24.7 \$1.5 \$1.0	40.00	6	<u>.</u>		œ.	67.	4.1		0000
Section Sect	45:0.	9	51.		٠.	567.	83	3.2	-0000°
55.5611.5 91.3 566.8 294.7 6.00 55.0611.5 91.3 566.8 294.7 6.00 55.0611.5 91.3 566.3 317.1 12.1 100001 77.0. 50.4 -88.2 -61.3 100001 100001 100001 100001 77.0. 50.4 -88.2 -78.1 77.6 571.6 317.7 11.0 100001 77.0. 50.4 -88.2 -78.1 77.6 571.7 317.9 8.2 100001 75.0. 50.1 -78.2 -78.2 77.6 570.7 316.9 6.0 100001 70.0. 50.1 -78.2 -78.2 77.6 570.7 316.9 6.0 100001 70.0. 50.1 -78.2 -78.2 77.6 57.9 100001 100001 70.0. 50.2 -78.2 -77.2 57.2 57.2 57.1 100001 70.0. 50.2 -77.2 57.2 57.2 57.2 57.2 100001 70.0. 50.2	SC 00.	•	51.			566.	58	N° N	.0000
000000 54.2 -6144 89.1 566.9 310.8 10.0 100000 70000 51.2 -601.4 89.1 566.9 311.1 10.0 100000 7000 51.6 -59.2 100000 100000 100000 100000 65.7 68.2 571.2 313.5 8.2 100000 65.0 68.2 571.2 313.5 8.2 100000 65.0 68.2 571.2 313.5 8.2 100000 65.0 68.2 571.2 313.5 8.2 100000 65.0 67.2 571.2 313.5 8.2 100000 65.0 67.2 571.2 313.5 8.2 100000 65.0 67.2 572.6 <td>55 J.C.</td> <td>\$</td> <td>_</td> <td></td> <td>:</td> <td>566.</td> <td>76</td> <td>6.8</td> <td>< 0000°</td>	55 J.C.	\$	_		:	566.	76	6.8	< 0000°
10,000 1	60.50	;	_:		ċ	566.	9	0	.0000
Marco Marc	65 NO.	2	ċ		÷	568.	17	~	.00001
10,000	70.00.	:			4	569.	23	4	.0000
100001	. Cr. S.1		·			571.	2	•	.0000
95.00.0 48.0 78.8 77.8 577.0 315.5 8.2 100001 95.00.0 45.8 -58.5 76.0 70.4 359.9 6.0 100001 95.00.0 45.6 -58.2 70.4 359.9 5.9 100001 95.00.0 45.6 -58.2 70.4 359.9 5.9 100001 95.00.0 45.6 -58.2 77.4 35.9 5.9 100001 10.00.0 45.6 -57.3 77.4 35.7 100001 20.00.0 37.8 -57.3 57.4 5.3 100001 20.00.0 37.8 -57.3 57.4 5.3 100001 20.00.0 37.8 -57.4 5.3 100001 20.00.0 37.8 -57.4 5.3 100001 20.00.0 37.8 -57.4 5.3 100001 20.00.0 37.8 -57.4 5.4 100001 20.00.0 37.8 -57.4 5.4	80.00	•	œ.		•	571.	12	6.6	.00001
76.0 570.7 316.9 6.6 100000 75.0 46.8 -58.5 7 7.6 570.4 316.9 6.6 1.000000 75.0 45.7 -58.8 7 7.6 570.6 320.4 320.9 5.0 1.000000000000000000000000000000000	85.70.	80	*			571.	13	8.2	.0000
95.5.0 45.7 78.8 77.8 570.4 322.9 6.0 100001 95.5.0 45.6 -58.8 70.8 370.4 322.9 6.0 100001 10.00.0 45.6 -58.2 6.0 571.2 353.2 5.9 100001 10.00.0 40.6 -57.9 6.0 571.2 353.2 5.3 100001 15.00.0 40.6 -57.9 6.0 572.0 17.4 5.3 100001 25.00.0 35.0 -57.0 6.0 572.0 22.7 5.1 100001 25.00.0 37.8 -57.0 6.0 572.0 22.7 5.1 100001 25.00.0 37.8 -57.1 57.2 22.6 5.2 100001 25.00.0 35.0 -55.1 57.8 57.6 57.0 57.6 100001 26.0 35.0 25.1 57.4 37.4 37.4 100001 27.0 37.0 27.8	• 00 06	•	m		•	570.	16	9.9	.0000
18:00.0 44.7 -58.8 77.2 57.0 44.7 -58.8 77.0 100000	95 00•	\$,	570.	22	0.9	.00001
150.00 45.6 -58.5 -58.5 -58.5 -58.5 -58.5 -58.5 -58.5 -58.5 -58.5 -58.5 -59.00 -57.5 -57	0000	•			~	570.	5	8.9	.0000.
10.00.0 4.56 -58.2 5.3 1.00001 25.00.0 41.6 -57.3 5.6 65.3 571.6 7.4 5.3 1.00001 25.00.0 138.7 -57.3 6.6 65.8 572.6 22.1 5.1 1.00001 25.00.0 38.7 -57.0 6.0 6.0 572.6 22.1 5.1 1.00001 35.0 -56.1 -56.1 5.1 1.00001 35.0 -56.1 -56.1 5.1 1.00001 35.0 -56.1 5.1 1.00001 35.0 -56.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 5.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 5.1 5.1 5.1 1.00001 35.0 -56.1 5.1 5.1 5.1 5.1 5.1 5.1 5.1 5.1 5.1 5	us 00 •	5	e eo		ငံ	570.	3	5.7	0000
1500.0 41.6 -57.9 67.3 571.6 7.4 5.3 1.00001 20.00.0 30.7 -57.0 64.0 572.8 22.4 5.1 1.00001 35.00 37.8 -57.3 64.0 572.8 22.4 5.1 1.00001 35.00 37.8 -56.7 64.0 572.8 22.6 5.4 1.00001 45.00.0 36.0 -56.1 56.1 57.8 573.2 22.6 5.4 1.00001 45.00.0 36.0 -56.1 56.1 57.8 573.2 22.6 5.5 1.00001 45.00.0 35.2 -55.7 5.6 57.8 57.4 33.1 5.5 1.00001 50.0 37.6 -55.7 5.6 57.8 57.4 37.1 5.5 1.00001 50.0 32.8 -56.2 5.2 57.8 57.8 37.1 5.5 1.00001 50.0 32.8 -56.2 52.5 57.8 57.8 37.1 5.2 1.00001 50.0 32.8 -56.2 52.5 57.8 57.8 57.8 5.2 1.00001 50.0 32.8 -56.2 52.5 57.8 57.8 57.8 57.8 1.00001 50.0 22.8 -53.7 5.8 57.8	10 JC	.;	•		·	571.	23	5.3	0000
25 U000 40.6 -57.6 65.6 572.0 14.7 5.1 1,0000 25 U000 39.6 -57.3 62.4 572.4 22.1 5.1 1,0000 35 U00 37.8 -56.7 60.4 572.8 23.6 5.6 1,0000 35 U00 35.9 -56.1 50.8 57.8 25.6 5.7 1,0000 40 U00 35.0 -56.1 50.0 57.8 57.0 35.1 5.6 1,0000 50 U00 35.0 -55.1 55.0 574.8 37.0 7.2 1,0000 50 U00 35.0 -55.4 37.0 37.0 7.2 1,0000 50 U00 35.0 57.8 57.0 37.0 37.0 1,0000 50 U00 35.0 57.8 57.0 37.0 10.0 1,0000 50 U00 35.0 57.8 57.0 37.0 13.1 1,0000 50 U00 35.0 57.8 57.0 37.	1500.	;			۲.	571.	~	5.3	00001
25 4.0 372.4 22.1 5.1 25 4.0 38.7 -57.0 60.8 572.8 23.6 5.4 20 3.0 38.7 -56.7 60.8 573.2 23.6 5.4 100001 30.0 36.9 -56.7 50.0 57.8 57.0 5.7 100001 46.00 36.0 -56.1 57.8 57.4 38.1 5.5 100001 50.0 36.0 -56.1 57.0 37.4 38.7 100001 50.0 37.4 -57.4 38.7 100001 50.0 37.6 57.2 36.7 100001 50.0 37.8 57.4 37.7 100001 50.0 37.8 57.4 37.7 100001 50.0 37.8 57.4 37.7 100001 50.0 37.8 57.4 37.7 100001 50.0 37.8 57.4 37.4 37.4 100001 50.0 37.8 57.4 37.4 37.4 100001 50.0 37.8 57.4 37.4 37.4 37.4 37.4 50.0 37.8 57.4 37.4 37.4 37.4 37.4 37.4<	20.00	÷			\$	572.	4	5.1	0000
38.7 -57.0 62.4 572.8 23.6 5.4 1.00001 35.0.0 35.8 -56.7 5.6 1.00001 1.00001 1.00001 35.0.0 35.8 -56.1 5.7 1.00001 1.00001 1.00001 1.00001 45.0.0 36.0 -56.1 5.7 1.00001 1.00	25 0.0	6			,	572.	\sim	5.1	0000
35.00.0 37.8 -56.7 5.9 573.2 23.6 5.0 1.00001 40.00.0 36.9 -56.4 573.6 26.4 5.7 1.00001 50.0 35.2 -55.4 38.7 5.7 1.00001 50.0 35.2 -55.4 38.7 7.2 1.00001 50.0 35.6 -55.4 36.7 37.7 1.00001 50.0 35.6 -56.5 36.7 1.00001 60.0 35.6 -56.5 36.7 1.00001 60.0 37.6 -56.5 37.6 12.6 1.00001 75.0 31.2 -56.5 36.7 10.0001 1.00001 75.0 31.2 -56.5 37.6 45.2 1.00001 75.0 31.2 -56.5 37.6 45.2 1.00001 75.0 31.2 -56.5 37.6 45.2 1.00001 75.0 24.2 57.4 57.4 57.4 56.0 10.0001 75.0 25.2 -53.5 44.0 57.7 56.0	30 00 ·	œ			ໍ້	572.	~	2.4	00001
56.9 56.9 56.5 57.6 55.7 1,00001 56.1 56.1 57.8 57.4 33.1 5.5 1,00001 56.0 35.2 -55.1 56.6 37.4 38.7 7.2 1,00001 55.0 34.4 -55.1 7.2 1,00001 55.0 1,00001 1,00001 66.0 35.6 -55.1 57.2 37.7 7.2 1,00001 66.0 35.0 -54.5 37.0 37.6 12.0 1,00001 66.0 31.2 -54.5 37.0 37.6 12.0 1,00001 66.0 31.2 -54.5 37.0 37.6 13.2 1,00001 75.0 31.2 -54.5 57.6 37.6 45.2 100001 86.0 31.2 47.2 57.6 47.2 10.0 10.0 86.0 20.1 20.2 20.2 13.1 10.0 10.0 86.0 20.2 20.2 <	35.00	~	•		ċ	573.	₩1	2.6	0000
55.00 36.0 35.1 5.5 1.0000 55.0 35.2 -55.7 36.4 38.7 7.2 1.0000 55.0 35.4 36.7 36.7 37.0 7.2 1.0000 55.0 35.4 55.2 36.7 8.7 1.0000 55.0 35.4 55.2 36.7 10.00 70.0 35.4 55.2 36.7 10.00 70.0 35.4 55.5 36.7 10.00 70.0 35.6 37.6 12.6 10.00 70.0 36.7 46.2 57.2 37.6 10.00 80.0 29.8 45.2 47.2 57.4 56.7 10.00 80.0 29.8 45.2 13.1 10.00 10.00 95.0 29.4 57.2 57.2 10.00 10.00 10.0 20.0 28.4 47.2 57.4 56.7 10.00 11.0 29.4 57.2 57.3 57.4 56.7 10.00 11.0 20.0 20.0	4 0 00	÷	Š		ċ	573.	v	2.7	0000
50.00 35.2 -55.7 1.00001 55.0 34.4 37.0 7.2 1.00001 55.0 35.4 37.0 7.2 1.00001 60.0 32.8 -55.1 8.7 10.6 1.00001 60.0 32.8 -54.5 35.6 35.6 10.6 1.00001 60.0 32.8 -54.5 57.6 37.6 13.2 1.00001 75.0 32.8 -53.7 47.2 57.4 57.6 13.1 1.00001 75.0 29.8 -53.7 47.2 57.2 13.1 1.00001 86.0 36.7 57.2 57.2 13.1 1.00001 86.0 36.7 57.2 57.2 13.1 1.00001 86.0 36.7 57.2 57.2 13.1 1.00001 86.0 36.7 57.2 57.2 13.1 1.00001 86.0 36.7 57.2 57.2 10.0001 10.0001 86.0 26.8 46.2 577.2 56.7 1.00001 86.0 26.8 46.2 577.2 56.7 1.00001 86.0 26.8 46.2 577.2 56.7 1.00001	45 00.	•	ŝ			574.	m	5.5	10000
55.0 574.8 37.0 7.2 1.00001 51.0 53.6 575.2 36.7 7.2 1.00001 55.0 32.8 -54.5 34.7 10.6 1.00001 55.0 32.0 -54.5 57.6 33.6 12.6 1.00001 75.00 30.0 -54.2 47.3 576.4 37.6 13.2 1.00001 75.00 30.0 -54.2 47.3 576.8 45.2 1.00001 80.00 30.0 -53.9 47.3 577.2 51.2 13.1 1.00001 80.00 29.6 -53.7 46.2 577.2 51.2 13.1 1.00001 95.00 29.1 -53.4 47.0 577.2 54.0 11.4 1.00001 95.00 27.1 -53.4 47.0 577.4 49.1 10.0 1.00001 15.00 25.2 -53.2 47.0 577.4 49.1 10.0 1.00001 15.00 25.3 -53.1 40.0 577.4 49.1 10.1 1.00001 15.00 25.3 -53.1 40.0 578.4 45.0 8.8 1.00001 15.00 24.1 -52.1 5	\$0 00°	Š	\$		÷	574.	αc)	5.7	10000
69.90.0 33.6 -55.1 8.7 1.00001 65.90.0 32.8 -54.8 12.6 1.00001 70.00 32.0 -54.2 12.6 1.00001 70.00 31.2 -54.2 13.6 13.6 13.00001 70.00 30.5 -53.9 47.2 576.8 45.2 13.1 1.00001 86.00 29.6 -53.7 57.2 57.2 13.1 1.00001 96.00 29.1 -53.5 46.2 577.3 57.2 1.00001 96.00 29.4 -53.5 46.2 577.3 55.8 12.2 1.00001 96.00 27.6 -53.5 46.0 577.4 56.7 11.4 1.00001 96.00 27.6 -53.5 46.0 577.4 56.7 11.4 1.00001 96.00 27.7 -53.3 47.0 577.4 56.7 11.4 1.00001 11.00 26.0 -53.3 47.0 577.4 56.7 10.1 1.00001 12.0 -53.3 -53.3 47.0 577.4 50.7 47.0 50.9 54.6 10.1 1.00001 12.0 -53.3 -53.1 47.0	55 00.	;			Ç,	574.	~	7.2	0000
55.5 34.7 10.6 1,00001 70.0 32.6 -54.5 12.6 1,00001 70.0 32.6 -54.5 12.6 1,00001 75.0 31.2 -54.2 40.7 576.4 37.6 13.2 1,00001 80.0 36.5 -53.9 47.3 577.2 51.2 13.1 1,00001 80.0 29.6 -53.7 47.3 577.2 51.2 13.1 1,00001 80.0 29.1 -53.5 44.0 577.4 56.7 12.2 1,00001 80.0 27.1 -53.5 44.0 577.4 54.0 11.4 1,00001 80.0 27.1 -53.3 44.0 577.5 54.0 11.4 1,00001 80.0 25.3 -53.3 41.0 577.6 49.1 10.1 1,00001 80.0 25.3 -53.1 41.0 577.6 49.1 10.1 1,00001 80.0 26.5 -53.1 41.0 577.6 49.1 10.1 1,00001 80.0 26.5 -53.1 41.0 578.0 9.5 1,00001 80.0 26.7 27.7 27.7 27.7 27.7	\$0.50°	'n	Š		٠.	575.	O	8.7	00001
70 32.6 -54.5	• Uri S 9	÷	•		2	575.	•	10.6	0000
75.5.0 31.2 -54.2 40.7 576.4 37.6 13.2 1.00001 60.00.0 36.5 -53.9 47.3 57.2 51.2 13.1 1.00001 60.00.0 29.8 -53.7 47.3 57.2 51.2 13.1 1.00001 95.00.0 29.1 -53.6 45.1 57.2 55.3 12.2 1.00001 95.00.0 27.6 -53.4 47.0 577.5 56.7 11.4 1.00001 11.00.0 25.5 -53.3 47.0 577.6 49.1 10.1 1.00001 15.00.0 25.9 -53.1 47.0 577.6 49.1 10.1 1.00001 15.00.0 25.9 -53.1 40.0 577.6 49.1 10.1 1.00001 20.00.0 25.3 -53.1 40.0 578.0 54.6 10.1 1.00001 25.3 -53.1 40.0 578.0 56.6 10.1 1.00001 25.3 -53.1 40.0 578.0 9.5 1.00001 25.3 -53.1 578.0 9.5 1.00001 25.3 -53.2 50.0 9.5 1.00001 25.3 -53.2 50.	70 00.	~	•		-	576.	M)	12.6	0000
60000 30.5 -53.9 47.5 576.8 45.2 13.1 1.00001 90.0 29.8 -53.7 13.2 13.1 1.00001 90.0 29.8 -53.7 13.1 1.00001 90.0 29.8 -53.7 13.0 12.0 12.0 12.0 12.0 12.0 12.0 12.0 12	75 .0.	;	•		°	576.	~	13.2	0000
65.70.0 29.8 -53.7 13.1 1,00001 90.0.0 29.1 -53.6 46.2 577.3 53.8 12.6 1,00001 95.00.0 28.4 -53.6 46.1 577.4 56.7 12.2 1,00001 90.00.0 27.6 -53.4 46.0 577.5 54.0 11.4 1,00001 90.0 27.1 -53.3 47.0 577.6 49.1 10.7 1,00001 11 C.S.0 26.5 -53.2 47.0 577.6 49.1 10.7 1,00001 12 C.S.0 25.9 -53.1 40.0 577.7 45.6 10.1 1,00001 20 C.S.3 -53.1 40.0 578.0 56.6 10.1 1,00001 20 C.S.3 -53.1 40.0 578.0 56.6 10.1 1,00001 20 C.S.3 -53.1 40.0 578.0 56.6 10.1 1,00001 20 C.S.3 -53.1 50.0 56.6 10.1 1,00001 20 C.S.3 -53.1 56.6 10.1 1,00001	80 00 ·	ċ	3		ď	576.	S	13.1	00001
90001 92002 92.000 28.4 -53.5 92.000 27.6 -53.4 90.000 92.000 27.6 -53.4 90.000 90.000 90.000 90.000 90.000 90.0000 90.	0. 0	•			۲.	577.	•	13.1	10000
95.06.0 28.4 -53.5 46.1 577.6 54.0 11.4 1.00001 10.00.0 27.6 -53.4 46.0 577.5 54.0 11.4 1.00001 11.0 26.5 -53.2 47.0 577.6 49.1 10.7 1.00001 11.0 26.5 -53.2 47.0 577.7 45.6 10.1 1.00000 15.0 25.9 -53.1 40.0 577.8 50.1 10.1 1.00000 25.1 26.2 -53.1 40.0 578.0 54.6 10.1 1.00000 25.3 -53.1 50.0 9.5 1.00000 25.3 -53.1 50.0 9.5 1.00000 26.0 24.7 -52.9 8.8 1.00000	90.UJ*	٠ د	M		ŝ	577.	₩,	12.6	0000
UO.C.D 27.6 -53.4 11.4 1.00001 UC.C.D 27.1 -53.2 47.0 577.6 49.1 10.7 1.00001 1(.C.D 26.5 -53.2 47.0 577.7 45.6 10.1 1.00000 15.C.D 25.9 -53.1 40.0 577.8 50.1 10.1 1.00000 20.C.D 25.3 -53.1 40.0 578.0 54.6 10.1 1.00000 25.3 -53.1 30.0 50.0 9.5 1.00000 25.3 -53.4 50.0 9.5 1.00000 26.0 24.7 -52.9 8.8 1.00000	95.56	å			·	577.	v	12.2	0000
USCO.6 27.1 -53.2 47.0 577.6 49.1 10.7 1,000001 1(CO.0 26.5 -53.2 10.1 1,00000 15.0.0 25.9 -53.1 40.0 577.8 50.1 10.1 1,0000 20.0 25.3 -53.1 40.0 578.0 54.6 10.1 1,0000 25.3 -53.1 30.1 50.0 9.5 1,0000 27.3.0 24.7 -52.9 30.0 24.1 -52.9 1,0000	· 0. 00	7.	'n		,	577.	4	11.4	.00001
1(C.0 0 26.5 -53.2 11 1,00000	02.00	,	M		۴.	577.	°.	10.7	.0000
15.0.0 25.9 -53.1 10.1 1.00000 2000.0 25.3 -53.1 40.0 578.0 54.6 10.1 1.00000 25.3.0 24.7 -53.0 30.1 578.1 50.0 9.5 1.00000 30.0.0 24.1 -52.9 38.1 578.2 42.0 8.8 1.00000	16.00.	3	3.		ď	577.	۶.	10.1	00000
20(0.0 25.3 -53.1 40.0 578.0 54.6 10.1 1,000000 55.3 54.7 -53.4 53.1 578.1 50.9 9.5 1,00000 30.1 578.1 50.9 9.5 1,000000 30.1 578.2 42.0 8.8 1,00000	15.0	Š	•		-	577.	ò		00000
25.73.0 24.7 -53.0 9.5 1.00000 30.0.0 24.1 -52.9 38.1 578.2 42.0 8.8 1.00000	. 0:10%	\$	٠.		ċ	578.	,		.0000
38.1 578.2 42.0 8.8 1.00000	C. 23	•	-53.		°	578.	Ö	•	.0000
	ָּהַ הַ	4	¥.28-		œ	578.	2		.0000

GEODETIC COORDINATES 32.40043 LAT DEG 106.37033 LON DEG	INDEX Of Refraction	1.000008 1.000008	1.000008 1.000007	1.000007	1.000007	1.000006 1.000006 1.000006 1.000006
6E0DETI 32.	SPEED KNOTS	80 80 Q	10.3	11.2	16.4	0.60
	WIND DATA DIRECTION S DEGREES(TN) K	3.00 13.00 0.00 0.00	356.8 2.5	7.6 359.0 352.5	345.0	342.4
0.8 1.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0	SPEED OF Sound Knots	578.6 579.1 579.5	579.9	580.7 581.1 581.6	581.9	
UPPFR AIR DATA 1030U29206 WHITE SANDS TABLE 6 Con't	DENSITY GM/CUBIC METER	2000 2000 2000 2000	34.5	32.4 32.4 1.5.4	20.5	2002 2002 2007 2007 2007 2007 2007 2007
	REL.HUY. Percent					
T T S L	TEMPERATURF 9 DEMPOINT FLS CENTIGRADE					
59.70 FEE	TEMP AIR Degrees	-52.5 -52.2 -51.9	-51.6	-50.9 -50.6	1.00.1	11111 96688 010000
LTITUDE 398 4 . 206	PRESSURF MILLIBARS	23.6 23.6 22.5	22.0 21.5	24.0 20.5 20.5	19.6	1387 14.05 14.05
STATION ALTITUDE 3989.NO FEET MSL 12 Apr. R4 0001 HRS MST ASCENSION NO. 206	GEOMETRIC ALTITUDE MSL FET	83500.0 84000.0 84500.0	850.00.0 8550.0	86000 86500 87000 87000	875 00.0	9 9 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0

STATION ALTITUDE 3969.FD FEET MSL 12 APR. 84 0001 HAS MST ASCENSION NO. 206

MAYLATORY LEVELS 1030U2U206 Umite Sands

6EODETIC COORDINATES 32.40043 LAT DEG 106.37033 LON DEG

TABLE 7

DIRECTION SPEED DEGREES(TN) KNOTS 17.1 26.7 39.0 45.4 35.6 35.6 32.7 36.2 5.6 11.5 WIND DATA REL.HUM. PERCENT 225. 225. 227. 227. 18. TEMPEPATURE AIR DEWPOINT DEGREES CFNTIGRADE E 0 0 0 -67.7 -65.8 -67.8 -06.0 -57.8 -64.1 -61.2 -57.9 -57.4 -53.7 -41.4 -04.1 PRESSURE GEOPUTENTIAL 10847. 70059. 74934. 39543. 42192. 45279. 48P87. . 4040 4253. 12083. 16438. 53301. 47395. 72003. 91870. 86516. 78019. 57817. 4781. 27 464. 60543. 63571. 80.0 80.0 60.0 60.0 MILLIPARS

•

AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 4010.40 FEET "SL 14 APR. 84 0230 HAS MST ASCENSION NO. 12

SERVICE SERVICE PROPERTY OF THE PROPERTY OF TH

SIGNIFICANT LEVEL DATA 17.502.20012

GEODETIC COORDINATES 32.86497 LAT DEG 106.49714 LON DEG

17.502.20012 vw 3n TABLE 8

REL.HUM Percent	NF F F F W W W W W W W W W W W W W W W W
ERATURE Dempoint Centigrade	1 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
TEMPE AIR Degrefs	11111111111111111111111111111111111111
GEOMETRIC Altitude MSL feet	44444444444444444444444444444444444444
PRESSURF WILLIBARS	# - BB V - A A A A A A A A A

~
.0.
z Z
ASCENSION NO.

FOREST PROPERTY PROPERTY PROPERTY SERVICES STOREST STO

GEODETIC COORDINATES 32.88497 LAT PEG 106.49714 LON PEG

UPPER AIR DATA 1737220312 Ne 30 TARIE O

	• • • • • • • • • • • • • • • • • • • •				TABLE 9			900	47/14 LON CE.
GEOME TRICALTITUDE	PRESSU	TEAIR	ERATURE DEWPOINT	REL.HUM. Percent	DENSITY GM/CUBIC	SPEED OF SOUND	WIND D	ATA Speed	INDEX Of
אר זי איי	FILLIBARS	œ	NT ICR A		FTE	NO T	GREES(T	N 0 1	REFRACTION
010.	875.	÷	-10.4	j	069	58	c.	0	0000
ټ ک	86U.	÷	;	æ,	044.	60,	۳.	•	.0002
. 00°	844.	?	₹.	Ď	58.	59.	ň		00024
0.3	829.	.	÷	Ď	017.	58.	M 1	•	\$ 2000.
933	814.	•	1.	•	97.	57.		•	2000
500	799.	ö		ģ	81.	56.	- -		.00022
000	785.	•	13.	٥	60	55.	•	•	.00027
Š	271.	•	•	پ	52.	54.	.64	•	.0002
00 00	756.	7.8	;		37.	53.	36.	•	0
S CO.	743.	•	*	ċ	22.	52.	23.	-	.00021
0.00	729.	•		,	07.	51.	16.	•	.0001
0	715.	•	•	2	93.	51.	. 70		.0000
900	702	•	5	္ပံ	78.	50.	95.	~	.00023
S	689.	•	:	ڻ	65	6.5	87.	۶.	.2000.
80	676.	•	12.	:	51.	48.	81.	~	02000.
٠ <u>٠</u>	. 499	•	\$	္ခံ	3.0	47.		;	.0001
900	651.	•	;	÷	26.	45.	81.	;	.0001
25.20.	639.	•	15.	Ġ.	14.	. 77	85.	۶.	.0001
3¢ 00•	627.	:	÷	٠ .	25	43.	87.	•	00018
3500	615.	۲.	17.	ċ	ċ	4.1.	89.	• •	.0001
• 000 •	603.	•	χ̈	ô	78.	40.	88	:	.0001
45.00	592.	;	20.	ė	67.	38.	86.	,	.00017
50.00•	581.	Š	:	ف	56.	37.	83	\$	00017
55.00	569.	•	25.	œ	£5.	35.	80.	÷	.00017
ون دن و	558.	တ	(J)	ÿ.	M	34.	76.	۲.	.0001
ر. ر. کو	547.	ċ	27.	,	22.	33.	74.		.0001
ייט טע	537.	9	'n.	;	-	31.	74.	•	001
75 S.C.	526.	-	5.5	.	00	30	75.	.	.00015
ဂ လ	516.	٠	٠, ر	ည်	9	29.	79.	ċ	.0001
35 00.	206.	3.	24.	ċ	70.	27.	81.	•	.00015
٠٥٥ ناخ	• >6 *	14.	72.	,	٠ ٧.	56.	ن 80	٠.	.0001
٠٥/ ٥٤	.384	15.	7.	'n	\$6.	25.	78.	-	.00015
0. 0.	470.	Ġ	ċ	۲,	5.7	24.	75.	ċ	.0001
.5.70	467.	•	7.≥•	;	34.	23.	73.	ċ	.00014
10.00	457.	17.	14.	ż	, 4 S	25.	7 3.	ċ	.00014
15 '0.	448.	n	\$	÷	14.	21.	7.4	e C	00017
• C r C •	439.	23.	37.	ċ	.40	19.	.72	ċ	. 1000.
5.5 3.0	.D	-21.5		16.3	2.568	618.3	4.275	0	
30 D.	421.	25.	÷	1 9.5	•	16.	76.	•	2014
35.5	412.	. 7.	£ U.	15.7	77.	15.	76.	~	. 0001 t

-42.3 -43.7 -45.1

4.6.5 -4.9.5

-50.7 -52.1 -53.5

5.6.4

-52.0 -53.4 -57.9 -64.9

-39.9

98.3 96.5 93.4

GEODETIC COORDINATES 32.88497 LAT DEG 106.49714 LON DEG

UPPER ATH DATA 1750220312 NW 30

STATION ALTITUDE 4010.40 FEET MSL 12 AP 2. 84

ASCENSION NO.

1.000178 1.000175 1.000123 1.000177

REFRACTION IND EX OF

SPEED KNOTS

WIND DATA DIRECTION SP DEGREES(TN) KN

REL.HUM. PERCENT

DEGREES CENTIGRADE TEMPERATURE Ala Dempoint

MILLIBARS PRESSURE

GLOME TRIC ALTITUDE MSL FEET

141.0 -41.0 -43.0

-45.6

1.000113

1.000109

1.000108 1.000106 1.000104

1.000102

6600000

.0000. .000099 40 C 0 0 0 0 . .0000

1.000091

444444 44444 44444 4444

.0000

1.0000.1 0400001

-56.0 -54.0 -58.5

-54.8

1.63-Je1.0 -63.5

4.00001

.0000.

46.3

1,0000.0000. • 0000.

.0000.

1.00034-1.000042

-47.0 -47.E

7.94-

-45.5

-46.3

1.0000.6

IN THE INTERPOLATION WAS USED HUMINITY VALUE AT LEAST ONE ASSUMED RELATIVE

STATION ALTITUDE 4010.40 FEET MSL 12 APR. 84 0230 HRS MST ASCENSION NO. 12

UPPER AIR DATA

ASCENSION A	LTITUBE 40 4 80. 12	10.40 FE 0230 HRS	ET WSL MST		103022001 NW 30	12		32.	C COORDINATES 88497 LAT DEG 46714 10N DEG	
					TABLE 9 (Con't				
OME TR	PRESSURE		ERATURE	2	WSITY	SPEED OF	٥	ATA	INDEX	
ALTITUDE	•	6 T V	DEMPOIN		M/CUB	SOUND	DIRECTION	SPEED	0,6	
	16.18AR	×	=		•	0	GRE	KNOTS	REFRACTION	
00.04	159	•			66	63.	86.	44.6	0000	
ڊي ر	155.	. 49			259.8	563.0	282.7	8.5.		
SC 25	152.	64.			ξ.	62.	80.	۲.	.0000	
55 50	248	40			47.	62.	80.		.00003	
້ ດີ	166.	92			42.	61.	82.		0000	
	141.	90			37.	60.	87.	ċ	.0000	
76.53.	137.	w ·			32	59.	91.	51.4	000	
75.75	9 () 1 ()	, 0,			25.	59.	94.	-	•0000•	
8000 1000 1000 1000 1000 1000 1000 1000	130	99			٠ د د	60.	92.	ċ	7000	
85 O	127.	9			14.	60	90.	ċ	.0000	
	174.	99			٠ د	60.	86.	۲,	7000	
95 CD.	121	•			ç.	59.	86.	•	70000	
ن د د د د د د د د د د د د د د د د د د د	118.	67.			Š	58.	87.	œ	0000	
65 30 ·	115.	67.			95.	58.	90.	8	* 0000	
ું. જ	112.	£5.			80.	60	92.	œ	,0000.	
15.00.	109.	9			8 4·	61.	93.	6 0	70000	
00.03	107	Š			70.	62.	95.	ċ	,0000	
C) (104.	49			74.	62.	97.	7	.0000	
0 , 5, 5	101.	۰			69	63.	90	۶.	0000	
35.0	66	•			65.	64.	98.	۲.	.0000.	
4C 70.	. 7 6	'n.			61.	94.	99.	•	.0000	
. 54	• 70	m			57.	. 79	66	,	10000	
50 Ju	92.	÷				64.	02.		.0000	
55 9.	.) ()	ů.			œ	65.	7.0	ċ	0000	
٠ د د د د د د د د د د د	. K	•			•	66.	13.	۲.	¥ 0000	
् । • ।	* ;	~ .			_•	65.	20.	2.	1000	
٠ ت ب	5	• \		•	*	5.5	×.	•	0000	
		•	•		•		٤٧.	•	0000	
	· ;	•	•••			53.	œ Or	•	0000	
• •	• ; ;	٠,				62.	0	æ	0000	
٠ ا ر		· ·						•	00003	
· ·	, 5,	•			•	52.	24.	·	0000	
ر. در ا	76.	7.77-			•	62.	31.	~	2000	
ن در	. 02	÷				53.	-	;	0000	
٠.	ۍ د	·				\$ 2	ċ.	۶.	20000	
15 J.	67.	C)			•	58.	\$6.	;	0000	
٠ ت د	65.					57.	Č	۲.	7000	
.5.	• •1 •0				•	57.	900	•	000	
•	c	2-14-				57.	1 2	ċ	2000	
• •	ر. *	1.04-			•	57.	8	0	Coons	

STATION AL	STATION ALTITUDE 4010.40 FEET MSL	10.40 FEE	7 #St		UPPER AIR DATA	DATA 12		GEODE 71	GEODETIC COORDINATES
J. AP.		02.50 HRS	TS.		20			32.	88497 LAT DEG
ASCENSION NO.	NO. 12				TABLE 9 Con't	'n't		106.	49714 LON DEG
GEOME TRIC	PRESSURF	16.4	TEMPERATURE	REL.HUM.	REL-HUM. DENSITY	SPEED OF	ATAU ONIN	A A B B B B B B B B B B	INDEX
MOL FEET	MILLIBARS	DEGREES	DEGREES CENTIGRADE		ME TER	K NO TS	DEGREES (TN)	KNOTS	REFRACTION
6.00.049	59.3	-59.7			8.96 8.96		286.3	19.6	1.000022
0.0.319		-58.5			0.46		297.7	18.7	1.000021
65000	56.5	4.72-			91.2	572.3	314.0	19.0	1.0000 20
655.0.0	55.2	-57.5			80.1		129.1	19.6	1.000020
\$6500°0		-58.5			87.1	571.2	342.0	19.1	1.000019
6650.0		6.85			85.5	570.2	358.7	17.6	1.000019
67000.0		-59.6			83.7	569.3	13.9	14.1	1.000019
675 . 3.0		-60.3			82.0		30.8	11.6	1,000018
630000		-63.5			87.0		48.7	8.6	1.000018
685 10.0		-60.0			78.0		59.1	6°6	1.000017
69673.0		-59.7			76.1		65.9	10.9	1.000017
595 7.0		-49.5			74.2				1.000017
7.00.00.0	7.77	-59.5			72.3	269.7			4.000016

STATION ALTITUDE 40.10.40 FEET "SL 12 AP4. 84 U230 HKS MST ASCENSION NO. 12

MANDATORY LEVELS 1730220012 N# 30

GEODETIC COORDINATES 32.88497 LAT DEG 106.49714 LON DEG

TABLE 10

PRE SSURE G	PRESSURE GEOPOTENTIAL		PATURE	REL.HUM.	0713	DATA
HILLIAAPS	FEFT	AIR Degrees C	DEWPOINT Entigrade	PERCENT	DIRECTION DEGREES(TV)	SPEED
P53.0	4829°	12.9	-10.1	19.	13.8	4.2
80°0°	• 679	10.3	-12.R	18.	11,3	
757.0	8241.	7.4	-14.5	10.	329.5	4.8
70 n 0	13795	6.7	- 10. A	31.		
€. U.S.9	12065.	1.2	-14.6	30.	282.4	,
0•∪09	14.150.	-3.7	-10.2	29.	288.0	32.1
457.0	16.791	6-8-	-22.7	32.	•	17.7
500.0		- 14.4	-24.4	42.	ر	42.0
457.0	21789	-18.6	-35.9	20.	~	40.1
0°u04	24.230.	0.97-	-42.2	20.	٥	43.8
450.0	27 464.	- 32 • 7	-48.5	19.	_	43.5
0.00%	*0.852.	-42.1			0	7.77
250.0	74.80X	-53.2			0	46.7
200.0	19396.	1.49-			•0	6.5.9
175.0	42050	-65.7			0	0.63
150.0	45144.	- 64 . 5			0	47.8
125.0	48709.	- 66.2			~	51.9
100.0	53213.	-63.6			~	53.2
80.0	57721.	-63.9			4	9.
7.0	60197.	-63.7			243.6	24.7
0.09	63537.	-60.3			261.7	20.2
0,05	57 294.	7.09-			31.2	-

AT LEAST ONE ASSUMED RFLATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

4751.33 FEET WSL 0407 HRS 457	
5	30
* 1 T U D E	
STATION AL	ASCENSION NO.

property transport transport transport

SIGNIFICANT LEVEL DOTA 1730370335 Jallen

GEODETIC COORDINATES 33.16712 LAT DEG 106.49511 LON DEG

TABLE 11

REL.HUM Percent	######################################
RATURE Dempoint Centisrade	111111111111111111
TEMPE AIR Degrees	
F GEOMFTRIC NLTITUDE N MSL FEFT	CUANTED CONTRACTOR CON
PPESSUR!	######################################

STATION ALTITUDE 4751.00 FEET MSL 12 FOR. 94 JAGN HKS MST ASCENTION NO. 76

SIGNIFICANT LEVEL DATA
103007034
JALLEN
TABLE 11 Con't

GEODETIC (OORDINATES 33.16712 LAT DEG 106.49511 LON DEG

PELSSURE GLOMETRIC TEMPFRATURE REL.HUM.
ALTITUDE AIR DEWPOINT PERCENT
MILLIDARS MSL FEET DEGRESS CENTISRADE

76.8 50190.7 -62.6 63.5 6.986.0 -60.2 62.9 6.765.7 -60.2 52.0 66649.5 -61.7 52.0 6644.5 -61.7 50.0 67441.5 -57.6 41.7 77147.2 -58.8 41.7 7715.1 -56.7 51.0 79177.3 -56.7 52.0 8475.3 -55.2 UPPER ATR DATA

T A T I U.	TITUDE 47	٠، ٥٥	1 "SL		UPPFR AIR D 17370703	ATA 6		=	COORDINATE
30 10 10 10 10 10 10 10 10 10 10 10 10 10		DAC" FRS	S		٦			33.	
? 	•				TABLE 12			ċ	
GEOMETRIC ALTITUDE MSL FEET	PRESSURF WILLIBARS	TEMP AI? DESREES	ERATURE Dempoint Centigrade	RFL.HUM. Prrcent	DENSITY S GM/CUBIC METER	PEED OF Sound Knots	MIND DA DIRECTION DEGREES(TW)	SPEED KNOTS	INDEX GF REFRACTION
₩	74.	۷.	3.	ø	967.	ر ده	ن د ن	•	00024
9	6 €	•	=	2	0.6.6.	59.	55.		12000
\leq	. 4.	•	<u>:</u>	å	<u>.</u> 65	59.	78.	•	.0002
ج	60	۲,	-1	÷	ე ე	59.	83.	:	. 500G.
65.03.0	314.4	10.7	m	16.5	3.866	656.7	295.8	14.6	1.0002 12
ς ,	66	•	5.	۲.	٠,	54.	31.	Š	.2000.
9		•	· 2	٠.	25.	53	35.	·	.0002
ָיי ק	70.	•	<u>.</u>	÷	5.3	54.	10.	÷	. 2000.
Ξ.	•	•	3	÷	3,	53.	30	œ	.2000.
S	6 2 •	•	ò	ં	ž1.	52.	23.		.2000.
5	25.	•	16.	۲.	24.	۶2،	17.	œ	. 2000
Ξ	15.	•	5.		92.	51.	38.	ċ	.200v.
3	05.	•	9	ŝ	79.	50.	95.	ċ	0002
5	6	•	· •	•	.50	48.	9.5	÷	-200C.
ζ,	76.	•	12.	2	5.	47.	74.	;	.2006.
5:	è.	•	15.	.:	-,	45.	73.	۶.	. noo1 °
5	-	٠.	₹.	œ	, c >	, 4,	74.	۲.	.00019
()	39.	•	17.	ď	14.	43.	75.	,	.0001
<u>.</u>	9	:	20.	5	0.4.0	42.	77.	₩,	.0001
2	15.	۲,		ċ	92.	6 0.	7 0	÷	.0001
	5	. .	25.	;	c on	39.	80.	÷	.00017
C 5 57	91.	\$,4.	ငံ	٥,9	6 0	9.1.	٠,	71000
5	30.	\$	5.	;	5.7.	* Ç.	82.	۲,	.00017
ر د د	63	7.4	6-0-6-	۶.	45.	٤5.	3 C.	'n	00017
	53.	œn.	٠ ت	÷	34.	33.	٥.	?	.00017
ر بر	47.	٠.	5.5	,	,,	32.	90.	٠,	0001 4
י כי בי	9	5		ယံ	٠, ر	-	င် က	ar o	.000.
7.	5.	:	. 2		5	29.	. 0	_	. rooj.
ر	7.	-	,	;	٠ د د	5 3	82.	,	.0001
02.0%	5.	16.	٦.	۲.	90.	27.	α; •	4	.0001
60.00	500	5.	. 4.	•	• • •	25.	در	•	.0001
67.36	٠ د	•	7.	. ,	5 p.	54.	70.	•	.0001
ر د ر	76.	. 5		ث	٠, ٠	54.	70.	٠.	1001
() ()	, ,	17.	-	۲.	35.	23.	70.	\$,00014
100	د ۲ ،	տ Մ	;	j	. 5.		((۶.	, 1351,
() 1	47.	5	٠ ١	ú.	٠.	30.	83	é	1001
	٠ ص	:	.,		40	۳,	er,	ŗ	1000
	60	•	74.	13	, ,	7.	c. az		1000
ر. د .	0.0	33.	٦,	`.	8,	15.		٠,	7001
C,	٠ د ۲	. 7 .		•	26	14.	er or)	•	1000

	UPPER ATR DATA	
IGN ALTITUDE 4051.33 FEET MSL	103001036	GEODETIC COORDINATE
15. P.C. 3407 HRS 457	JALLEN	33.16712 LAT DE
461 OK 40. 36	TABLE 12 Con't	106.49511 LON DE

TENNING MARKET STATES TO THE STATES OF THE S

100 HRS 45.7 100 HRS 45.7 100 HRS 45.7 100 HRS 66.8 100 HRS 96.8 10									•	
TABLE 12 CON T. PRESSURE THERRITHER RELATION PLANSITY SPEED OF DIRECTION SPEED OF DIREC	L ;		407 E04	7		JALLEN			, ,	16712 LAT DE
The Feel Willier Free Friends Free Friedding Free Frieddi		• 02				ABLE 12	_		90	FYSTT LON DE
25.5.7 - 25.9 - 25.5.	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	PRESSUR ILLIBAR	TEM AIR EGREES	ERATURE Dempoint Centigrad	EL.HUM FRCENT	ENSITY M/CUBIC METER	PEED O Sound Knots	WIND D DIRECTION EGREES(TW)	TA SPEE KNOT	IND EX OF EFRACTIO
1000 1000		33.	75	5.	٠,	ας.	12.	80.	en	.000
17.00		95.	96	×	2	50.	:	78.		.0001
379.0 379.0 <td< td=""><td></td><td>87.</td><td>8</td><td>•</td><td>Ġ.</td><td>6.0</td><td>13.</td><td>77.</td><td>-</td><td>.0001</td></td<>		87.	8	•	Ġ.	6.0	13.	77.	-	.0001
7. 35.2.		62	23.	65.	š	.0.4	08.	75.	٠,	.0001
25.3. 2.45. 2.45. 2.59 512.9 605.5 573.7 52.5 1.0001 25.2. 2.42. 2.40. 2.59 512.0 605.5 573.7 52.5 1.0001 25.2. 2.42. 2.40. 2.50 51.0 605.5 573.7 52.5 1.0001 25.2. 2.42. 2.40		70.	33.	43.	;	51.	07.	74.	3.	.0001
7. 355.3 - 77.4 - 46.4 - 22.9 514.0 604.5 573.7 52.5 1.0001 7. 355.3 - 77.5 - 47.5 - 21.0 494.9 601.2 570.4 568.8 57.5 1.0001 7. 355.8 - 77.5 - 47.5 - 21.0 494.9 601.2 570.4 568.8 57.5 1.0001 7. 355.8 - 77.5 - 75.5 - 75.5 - 75.5 1.0001 7. 355.8 - 75.5 - 75.5 - 75.5 - 75.5 1.0001 7. 356.8 - 75.5 - 75.5 - 75.5 - 75.5 1.0001 7. 356.8 - 75.5 - 75.5 - 75.5 - 75.5 1.0001 7. 356.8 - 75.5 - 75.5 - 75.5 - 75.5 1.0001 7. 356.8 - 75.5 - 75.5 - 75.5 - 75.5 1.0001 7. 356.8 - 75.5 - 75.5 - 75.5 - 75.5 1.0001 7. 356.8 - 75.5 - 75.5 - 75.5 - 75.5 1.0001 7. 356.8 - 75.5 - 75.5 - 75.5 1.0001 7. 356.8 - 75.5 - 75.5 - 75.5 1.0001 7. 356.8 - 75.5 - 75.5 - 75.5 1.0001 7. 356.8 - 75.5 - 75.5 1.0001 7. 356.8 - 75.5 - 75.5 1.0001 7. 356.8 - 75.5 1.00		53.	-	. 5.	ň	2.	35.	74.	۶.	.0001
7. 347.7		55.	2 :	. 97	,	14.	. yc	73.	۶.	,0001
75.5.3 - 35.6.0 - 45.1 - 21.0		47.	¥.	. 27	÷	05.	93.	71.	۶.	1000
73.3.0		•07	36.	. 67	÷	9.5	9.	70.	•	1000
1955.8 -77.0 -51.9 19.4 467.5 598.7 268.8 56.2 1.0001 19.4 472.5 19.5 1		33.	3.	50.	ဝံ	° 8	00	68		1000
118.7		75.	17.	7.	ċ	ć,	98.	68.	•	0001
10001 10001		18.	8	*	6.1.	72.	97.	60	\$	2001
10000		11.	ċ	۶9.	6.2*	ě.	95.	60	•	0001
2001		0.4	:	66.	5	57.	93.	69	Š	.0001
286.8 4 58.9 58.0 10000 272.1 48.1 586.7 588.1 558.1 558.0 10000 272.1 48.1 586.3 568.4 558.0 10000 272.1 48.1 586.3 568.4 558.0 10000 272.1 48.1 586.3 568.4 558.0 10000 272.1 48.1 586.3 58.2 568.4 558.0 10000 272.1 48.1 586.3 58.2 58.2 58.2 10000 272.2 47.9 45.3 58.2 58.2 58.2 10000 272.3 46.3 57.3 57.3 57.3 57.3 10000 272.3 47.4 57.5 57.3 57.3 57.3 57.3 10000 272.3 47.4 57.5 57.3 57.3 57.3 57.3 57.3 57.3 57.3		98.	2.			50.	-	60.	\$.0001
28.8.4		91.	2			67.	89.	68	;	0000
272.3		94.	۶.			55	38	58.	\$	0000
272.1 -68.1 265.9 -40.5 265.9 -40.5 265.9 -40.5 265.9 -40.5 265.9 -40.5 265.9 -40.5 265.9 -40.5 265.2 -40.6 27	Ç	3	9			5.8	ά.	58.	٠.	2000
265.9 -49.5 265.9 -40.5 259.8 -50.6 257.2 -50.6 260.1 56.7 260.2 570.1 560.9 260.1 56.7 260.2 570.1 560.9 260.2 57.2 260.3 56.7	Ç	72.	ŝ			21.	*	φ.		• 0000
259.6	c.	65	ċ				٠ %	٠ م		0000.
253.6	ç	× 6 ×	ċ			٠,٠	3.	60	;	• 0000
247.9 -53.6 262.0 -64.6 27.2 247.9 -53.6 27.3 27.3 27.3 27.3 27.3 27.3 27.3 27.3		53.	52.			00.	00.	60	.	0000
242.0 -44.8 275.4 -572.6 275.5 -46.1 275.5 -47.4 275.6 -573.9 275.6 -573.6 275.6 -573.6 275.6 -573.6 275.6 -573.6 275.6 -573.6 275.7 -573.6 275.8 -573.6 275.8 -573.6 275.8 -573.6 275.9 -773.6 275.9 -773.6 275.0 -773.6 275.0 -773.6 275.0 -773.6 275.0 -773.6 275.0 -773.6 275.0 -773.6 275.0 -7		47.	53.			9.1	77.	70.	۲.	0000
276.3 -56.1 225.3 -57.4 225.3 -58.7 225.3 -58.7 225.3 -58.7 225.3 -58.7 225.3 -58.7 225.3 -58.7 225.3 -58.7 225.3 -52.9 225.4 -52.9 225.5 -52.9 225.5 -52.9 225.7		• 2 9	٠,			96.	3.	71.	ċ	.000.
255.3 -58.7 51.9 1.0000 225.3 -58.7 51.9 1.0000 225.3 -58.7 51.9 1.0000 214.6 -50.9 52.1 1.0000 214.6 -50.9 52.1 1.0000 214.6 -61.9 52.1 1.0000 214.6 -62.9 52.1 1.0000 214.6 -62.9 52.1 1.0000 214.6 -62.9 52.1 1.0000 214.6 -62.9 52.1 52.0 52.1 52.0 52.1 1.0000 214.6 -62.9 52.1 52.0 52.1 52.0 52.1 52.1 52.1 1.0000 214.6 -62.9 52.1 52.1 52.1 52.1 52.1 52.1 52.1 1.0000 214.6 -62.8 52.1 52.1 52.1 52.1 52.1 52.1 52.1 1.0000 214.7 -62.8 52.1 52.1 52.2 52.8 52.1 1.0000 214.7 -62.8 52.1 52.1 52.2 52.8 52.1 1.00000 214.7 -62.8 52.1 52.2 52.8 52.1 52.1 52.1 52.1 52.1 52.1 52.1 52.1		9.	٠ د			20.	, ,	72.	٠,	. 3050
255.3 -59.7 -50.9 -60.9 -60		6	۲2.			٠ د ۲	۶2′	73.		. ၁၁၅၁
15.000 276.2 55.1 1.0000 276.2 55.1 1.0000 276.2 55.1 1.0000 276.2 55.1 1.0000 276.2 55.1 1.0000 276.6 57.0 57.0 1.0000 276.6 57.0 57.0 1.0000 276.2 57.0 57.0 1.0000 276.2 57.0 1.0000 276.2 57.0 1.0000 276.2 57.2 1.0000 276.2 57.2 1.0000 276.2 57.2 1.0000 276.2 57.2 1.0000 276.2 57.2 1.0000 276.2 57.2 1.0000 276.2 57.2 1.0000 276.2 57.2 1.0000 276.2 57.2 1.0000 276.2 57.2 1.0000 276.2 57.2 1.0000 276.2 57.2 1.0000 276.2 57.2 1.0000 276.2 57.2 1.0000 276.2 57.2 1.0000 276.2 57.2 1.0000 276.2 57.2 57.2 57.2 57.2 57.2 57.2 57.2 57		55	3.9			4.	70.	74.	:	.0000
2094 -41.9 2094 -41.9 2094 -41.9 2094 -41.9 2094 -41.9 204.3		15.	٠.			50.	66	۶.	۲.	000u•
20944 -41.9 204.3 -62.9 204.3 -62.9 204.3 -62.9 204.3 -62.9 204.4 -63.9 204.5 -64.0 204.5 -64.0 204.5 -64.9 204.5 -64.9 204.7 -63.0 204.7 -63.0 204.9 -63.0 204.9 -63.0 204.9 -63.0 204.9 -63.0 204.9 -63.0 204.9 -63.0 204.9 -63.0 204.9 -63.0 204.9 -63.0 204.9 -63.0 204.9 -64.9 204.0 -64.9		14.	50.			۲,	57.	77.		.0000
-0 1994 -63.9		60	٠.				56.	70.	,	0000
-0 199-4 -63.9		نوه	5.2			٠ ۵ ۶	, 4.	80.	۲.	0000
.0 194.5 -44.6 55.7 1.0000 1.0000 1.0000 1.0000 1.0000 1.0000 1.0000 1.0000 1.0000 1.0000 1.0000 1.0000 1.0000 1.0000 1.0000 1.000000 1.00000000		65	*)			3,	53.	582	\$	0000
.0 189.7 -45.7 .1 185.0 -46.0 .0 186.4 -57.5 1.0000 .0 176.6 -47.0 -4		64.	* 4 .			5.7	62.		۶.	0000
185.0 -45.0 . 1.00000 . 1.000000 . 1.000000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.000000 . 1.000000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.000000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.000000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.00000 . 1.000000 . 1.00000 . 1.000000 . 1.000000 . 1.000000 . 1.000000 . 1.000000 . 1.000000 . 1.000000 . 1.000000 . 1.000000 . 1.000000 . 1.0000000 . 1.000000 . 1.000000 . 1.000000 . 1.0000000 . 1.00000000		c a	45.			•	51.	35.		0000
19 19 19 19 19 19 19 19 19 19 19 19 19 1		\$	•				53.	36		0000
176.6 -47.6 1.000 176.6 -47.6 1.000 177.6 -64.9 26.1 562.2 288.7 56.7 1.000 177.6 -42.3 1.000 177.7 565.1 56.3 1.000		٠	47.			, v	5.9	7 00		0000
267.1 562.2 298.7 56.7 1.0000 177.4 -62.3 26.7 1.0000 177.4 -62.3 1.0000		,	. 7			, ,	0	u C	' '	
777. 747.4 -42.5 1.0000 277.7 565.1 288.7 555.3 1.0000			•			,	• · ·	ο α Ο α	• ﴿	
10100 P 0 40 C 616 1 101 C 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1						7 C	• • • • •	• • • •	•	
		•					•	• 0	•	200

AT LEAST OVE ASSUMTS RELATIVE HUMINGTY VALUE WAS USED IN THE INTERPOLATION.

5	0407 HRS 45T	
ALTITUDE	2 4	
TATION	. 3p 2.	• • • • • • • • • • • • • • • • • • • •

UFPER AIR DATA

∓	1.1 2		1.0	۲	۲	×	5	~	ž	۲_	~	2 :	<u> </u>	٤:		•	~	7		$\overline{}$	\sim	$\overline{}$	$\overline{}$	\sim	71.0	~	~ 4	~ 4	~ ^	` ~	`~	•	` ~	\sim	$\overline{}$	\sim	$\overline{}$	$\overline{}$	$\overline{}$	-
CUORDIN 5712 LAT	ה ה	INDEX	CT.	9	000	.000	000	, DOC.	000	.000	8	000	5000			000		0	ι,	.000	۲,	-	9	~	1.303	٠,		٠,	•	•			•	\sim	•		.,	٠	•	-
	c C	1 A	2 2	ζ.		•		,	ċ	~	•	•	٠.	•	• •				\$	3.	7.		\$	-	25.5	ζ,		•		•		•			•	•	•	•	•	
			ن د	. 2	•	\$	7.	ç.	ž.	5.	~	·	4 :	٠,	707		. v.	9	7.	.00	30.		00	66	400.7		2.	20	· (•		. 4	-	0	59.	000	\sim	۴.)7.	
	Con't	SPEED OF	KNOTS	6	65.	•	63.	52.	51.	61.	€0	90	• •	2 6	. a	5 2	58	58.	59.	60.	60.	61.	<u>61.</u>	61.	551.9	62.	63.	54.		• u =	,	, 4 , 4	5.5	65.	55.	8	58.	ج. دن	68.	
16.30,700 JALL ^{FR}	TABLE 12 C	DEMOTITY	METER	, Q	, ,	52.	4.6		35.	SO.	25.		• v	• • •	ċ		C O	85.	C P	75.	71.	÷ Ç	۲.	•	154.2	•	V.	•		٠,	•	٠,	, ;		·	۶.	¢.	134.5	,	
•		REL-HU4.																																						
1 ~SL 45 T		ERATURE ACCOUNT	45 I I N								•																													
51.70 FEE		1 E 4 P		•		S .	4	4	3	5.	\$?	\$		6	• •	80	en W	٨٧.	. 7 .	56.	65.	55	55.	65	\$	7	٠ س	۶.	• • • •				· ~		÷.	٠C٠	-43.1	$\overline{}$	C	
TITUDE 47	٠ •	FRESSURE	WILLIBARS	0		_	48.	, ,	•07	7.	7			•	• - ¤		12.	50	30	<u>ر</u> و.	5		•	,	0.56	ċ	٠.		• • •	• 0	• •		•		,	'n	•	٠'n	•	
	, r i a c i 04	GEOMETS C	1 1 2 2		6.5		55:0	Seg	0. S	الداري	ر ر س	50.0	E: C			ے : کا د	40.01	0. 31	ر د	25.39	0000		S G	(1, 5;	\$5010.0	SS 33	ເ ເວ	ر . د ر	ر د د	, c	, E); se	ر n)	بر ت	10.01	15.37	ر رز	ر: د:	

KOCOSSI I SSSSSI RESERVE I KIKKIKA CKAS

UPPER AIR DATA

A 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	TITUDE 4)	51.33 FEET WSL G407 HRS W.J		10300×33 JALLEN	35		33	C COOR
50 I c N 21 Cd	• 0 •			TABLE 12	Con't		•	49517 LON DE
GEOFF TRIC	PRESSURE	TEAPER FILLS	REL.HUM. PFRCFNT	new SITY	SPEED OF	MIND DA	4	INDEX
SL FEE	MILLIBARS	ES CENTIGRA		METER) Z	5(1	KNOTS	REFRACTION
לטנז		-63.9			67.	4.7		.0000-
0.154				٠.	57.	80	•	. 3000 z
S	•	-61.7		•	99	,	ċ	.0000
S . 3		-51.4		٠,		۲.	င်	.0000
	m,	-61.2		. .	· .	٠,	•	, 0000
	٠.	D. (0)		٠,		K. 6	: 0	10000.
0.000 0.000 0.000 0.000	- 0 - 0	5 · N · I			577.0	20.00	o • 6	
7 2 2		7.25		ά.	72.		•	.0000
SS 13	~	7.2		\$	2	Ġ		00000
6336	÷	-57.0		,	72.	c (•	10000
02.56		7.7.4		٠,	72.	27.6	•	.0000.
gg gg	•				571.	ď	•	0000
06 vi)	~	5.8.5		٠,	571.	Š		L 00001
	մ։	-58.6		٠,	570.	<u>.</u> ,	ġ,	10000
	<u>.</u> .	7 · 6 · 6 · 6 · 6 · 6 · 6 · 6 · 6 · 6 ·			577	م ن		.0000
 	• •)		, ,	574	• ^	•	
\$ 0 C		- 10 10 10 10 10 10		٠,	573	56.1	•	10000
35.30	~	156.8		ď	573	Š		0000
ינו טי	•	-55.8		ď	573.		•	0000
C 83	Š	-56.9		•	573.	ċ	•	.0000
د	•	5.9		•	572.	۲,	٠.	5000
٠.	•	0.5		,	573.	;	•	. 10001
	•	2.95-		٠,	573.	'n,	•	,0000
יי היי טיי היי	•	, c		٠,	, , ,	• • •	•	
		* · · · · · · · · · · · · · · · · · · ·		707	575	•	13.5	1,000011
C. 79		-54.0		•	575	~		10000
	•	2.7.			575.	4	•	.0001.
دات ياد	9	2.75-		(***)	575.	,	ċ	10000
(; j6	œ	6.48-		6.22	575.			. noog
: 00		-55.7		•	575.	. 7.2	٠,	13301
(·	•	- 45.		42.0	575.		•	0000
ان دا	ė	;		4.1.	575.	-	5	บองจอ
٠,	٥.	•		c°.	575.	<u>-</u>	·.	2000
	Š	v		o*	577.	23.	•	רטפסר
5	•	-53.6		K a M	577	~	•	רסספר
ت. د •	23.9	U 1		•	5 7 8 .	7.7		00000
C .	M	٠,		34.9	579.			000

STATION ALTITUTE SET SET ON NO.	LT1TUBE 47: 4 80. 36	STATION ALTITUDE 4751.79 FEET MSL 12 app. e4 C4C7 HRS MST Asception No. 76		UPPER AIR DATA 1030070356 JALLEN TABLE 12 Con't	DATA 136 Con't		6E00E71 33. 106.	GEODETIC COORDINATE 31,16712 LAT DE 106,49511 LON DE
GEOWETRIC PRESSUALITIONE ALTITUDE PSC FEET WILLIBA	GEOMETRIC PRESSURE ALTITUDE MSL FEET WILLIBARS	TEMPERATURE AIP D'APOINT DESRIES CENTIGRADE	AFL, HUY. Percent	AEL.HUM. DENSITY SPEED OF PERCENT GM/CUBIC SOUND METER KNOTS	SPEED OF Sound Knots	MIND DATA DIRECTION SPEED DEGREES(TW) KNOTS	SPEED KNOTS	INDEX OF Refraction
845 (C) (L) (L)		22.8 -41.5 22.3 -51.0		W. 4.	35.8 580.0 54.9 580.7			1.000008 1.000008

STATION ALTITUDE 4751.33 FEET MSL 12 AFR. P4 - 2437 HRS MST ASCENSION NO. 36

MANDATORY LEVELS 1m3j070736 Jallen

TABLE 13

GEODETIC COORDINATES 33,16712 LAT DEG 106,49511 LON DEG

PRESSUDE GE	GE OP OT ENTIAL	1	4PERATURE	E .	٥	ATA
	FEET	AIR DFGREE	DEWPOINT CFNTIGRADE	PERCENT	DIRECTION DEGREFS(TV)	SPEED
853.9	4.21.	13.3	-13.2	17.	76.	•
93A.3	60	8.5	7	17.	5	15.8
750.9	5,7,9	7.7	•	16.		
737.9	മ	0.7		0	6	င်
657.0	12.68	2.	-	œ	74.	~
500.1	14135.		•	\$	S.	
457.0	S	7.6-	~		80	
130.3	13754.			Ø		64.3
0.051	21.52.	-19.5	*		81.	
400.0	100	-26.3		4	70.	
450.0	()	-33.1	~		72.	~
400.0	0	-42.1			69	S
25 0.0	7475n.	-53.1			73.	
200.0	•	-63.8			\$ 2.	•
175.9	45.04.	-66.5				
159.9	45115.	-63.8			87.	80
125.0	48757.	-65.7			9.4	~
100.0	.3174.	-65.5			3	~
C. C.	-	-65.1			34.	·
0.7	•	-62.4			50.	
67.0	13494.	7.69-			53	6.3
55.0	_	-57.5			C	
C*U*	-	- 55.7			50.0	
30.0	27822	- 54.5			-	~
24.3	18.5	-53.7			~	

:

AT LEAST ONE ASSUMED RELATIVE HUMINITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 5989.00 FEET MSL 1. APR. B4 US." HAS WST ASCENSION NO. 207

SIGNIFICANT LEVEL DATA 1730070257 PHITE SANDS

GEODETIC CUORDINATES 32.4.0.43 LAT DEG 106.37033 LON DEG

TABLE 14

	98578	95.140.772.0	HIT IS
	TITUDE	IR DEMPOIN	PERCENT
FILLIDARS	JL FEF	EFS CENTI	
77.	7 4 7	.7 -10.	3
55.	4	.2 -13.	
59.	344.	.2 -13.	0
3.5	.626	.11.	0
6.3	.140	.613.	173
0.00	3166.	.9-	•
a.60		.1 -17.	<u>.</u>
15.3	1.35.	.5 -16.	
1.1.	4:41.	.52- 7.6	-
15.9	. 460	13.0 -21.	~
C.C0	.042	6.9 -23.	~
6.44	1772	3.1 - 13.	•
0.0	4.07.	26.1 -40	.0.6.
9.70	640.5	32.3 -45.	,
6.8.4	7325.	24.1 -47.	4
13.8	9914.	39.1 -52.	2
.0.0		42.2)
0.0	4805	52.	
78.4	6709.	57.	
(3.0)	3534.	62.	
72.0	0.360.	79	
27.5	11670	51.	
20.	7	~ ~	
15.9	10.00	67	
~ · ~	1367	9 7 9	
ດ ເ	35.75	5.5	
5.8	6352	57.	
0.0	2704.	0.0	
S, R	5032.	S S	
2.1	6675	55.	
0.0	7676.	ς. Θ.	
7.0	. 104.	۰9۷	
7. 0	2147.	56.	
0.0	. 5 . 5 .	52.	
9.1.	3	53	
4.1	1 16 1	50.	
٧.	2.60.0	-51.3	
ر • ت	7156.	6.9	
	4 1 4	6.3	
10.01	251	42.	

-			
	STATION ALTITUDE 3989.00 FEET PL	P. 84 US.5 HKS MST	ASCENSION NO. 207
	STATI	1. KFP. 8.	A C C R

GLOME TRIC FLT1TUDE MJL FFET

BOPFK AIR DATA 1736020207 WHITE SANDS

GEODETIC COORDINATES 32.40043 LAT 04.6 106.57037 LDN 04.6

16	-	AEL.HUM.	PENSITY	SPEED OF	AU OVIN	ATA	INDER
A 1 P S DEGREES	CENTIUPADE	L .	GM/CUETC METER	SOUND	DIRECTION DEGREES(TW)	SPEED	OF REFRACTION
~	-10.3	ċ	1068.1	959	ď	6.6	1, 1005.1
~~	-10.3	15.0	1007.8	0.59.0	0°5~	0	1.0002-1
12.2	-10.7	\$	1050.3	550	4.	11.3	2000
~	-10.5	19.0	1031.7	£5.	÷.	12.5	2000
4-	-	,	1014.4	647	~	16.3	1.0002 *8
11.4	÷		997.3	657	r	12.4	1.000234
•	-11.7	7.00	963.5	5:4	·	7.0	1.000.2
	-12.0	ů.	904.3	056		2.4	3000
0.5	-1	ŝ	950.0		7 *	5.3	(3)
3.6	-12.1	21.5	Ļ	6.4.		0.80	03021
7	-13.1	.:		. v	•	10	12000
9	0.01	÷	- + f C	ζ,	ري	· .	2000
7.0	-11.5		391.7	5	\$	16.7	0005
4.5	3.6-	2.64.2	861.3	5.4	37	18.0	1.000211
•	-11.7	÷	364.1	•	*1	21.3	2000
2.7	-15	0.5.5	855.1	49	•	23.9	3.000250
7.5	-17.4	24.3	841.7	979	75.	24.1	1.000195
1.5	-1c.	25.1	827.8	945	7.2	23.5	1.009193
-	-17.	5.5.7	315.3	644.3	7 K.	21.6	1.000150
-1.		76.5	**.0a	٥	•	21.0	1.0001 "7
	-10.0	56.9	791.1	041.6	ഹ	21.9	1.0001 23
-5.5	-19.5	27.5	772.2	640+3	1.485	22.5	1.000183
4.41	J•62-	7 00 1	767.6	678.9	37)	24.1	1.00017
-5.	4.05-	;	756.1	6.77.6	70	26.3	1.000175
-6.0		*	244.3	635.2	\sim	0	1,000172
٠. ٧-		ŝ	733.7	6.759	~	39.5	1.000149
か。 此一		9*1	7.2.8	633.5	\sim	•	000
-10.1		ż	71.71	632.1	~	~	• .
-11.5		s.	701.8	6.0°4		•	.0021/
-12.3		ċ	691.6	528.8	278.5	-	-
-14.1	ۍ. ۱	۲.	81.	627.3	~	~	1.6001.7
S	-54.1	Ĵ	۲.,	6.556	O	~	1.000154
-15.1	-55.7	'n	۶۶,	624.8	70	•	000
~	-37.4	`	?;	673.7	8	~	001
	1.6.1	7.00	•	622.6	າກ	S	1.003145
•	0.5.	ń	,,	621.4	α α	•	1.000142
1-13-1	0.4	;		620.3	ກ	35.1	5
٠	77.5%	0.0	90	619.3	285.0	4	1.000177
-21.3	N . OK.		۲.	617.6	'n	55.0	5
10.0							

**3.6

4.04

6.47--46.6

-35.9 -38.1 -39.4

271.3 273.1 273.4 273.6

.0000°2 .000001

.000349 .00003 2000c. .335083 0 0000 ª . 6300 78

• 3000 se

45.5

274.3

274.7 274.5 274.7

273.7

-57.3

16.2

-56.5

-58.5 -59.4 -62.5

30.3 **60.7** 56.0 81.5

0.00.000

25.4

4.05 30.0

-63.0 -54.0 -43.7

-63.4

77.1

-62.1

-61.4

21.20 21.50

Q+00 Ja 0.31 241

-48.5 -56.0

-54.0

5.877

345 .0 .0

0.600

-55.1

242.9 237.0

.00000

<7.000° 5,0000. . 2000.4

. 0000

272.2

٠٠٠ / د 734.5

. 000°. . 2000. 79000°.

. .

*U000)

66 00000 .00000

6.6 39.8

40.4 47.1

5.475

275.2 275.3 275.4 275.7

.000101

760000. .0000°

GEODETIC CUORDINATES 32.40043 LAT DEG 136.37333 LON DEG

UPPER AIR DATA SUNAL BITHE

STATION ALTITUDE 3959.00 FEET MSL 12 APK. 3. 0525 HAS MST

د.،

ASCENSION NO.

1.000135

REFRACTION

INDEX Ö

> SPEED KNOTS

DEGREES (TY) DIRECTION

WIND DATA

REL.HUM. Percent

DEGREES CLATICRADE

WILLIBARS PPESSURE

DEMPOINT

AIA

TEMPERATURE

GEOME TRIC

ALTITUNE MSL F ET

000124 000124 000122

41.0 37.4 37.1

22.28 4.9.2 22.28 4.9.3 22.26 6.3.3 22.26 6.3.3 23.56 7.4 23.56 7.4 23.56 7.4 23.56 7.4

.000116

38.7 39.5 40.1

3.54-**5.6** €

-32.5 -33.5

350.4 348.E

27550.0

-34.5

335.9

180 - 180 -

-26.5

245.0 245.0

-24.3

211000.

.1000. .000110 .000106 .000104 5" 1000 .

.000158

268.0

250.4

WAS USED IN THE INTERPOLATION AT LESST DOL ACSUMPO OFLATIVE HUMINITY VALUE

APPAINTSSSSSSINGER TO THE SECOND SECO

**************************************	786.7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
666.66 666.66 667.66	2.2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
66664 666644 66664 66664 66664 66664 66664 66664 66664 66664 666644 66664	665.4 66
65.66 65.17 65.18 65.19 65	65.6 64.6 64.6 64.6 64.6 64.6 64.1
64.6 64.6 64.6 63.6	64.6 64.6 64.6 63.6 64.6
62.0 63.0	62.0 63.0 63.0 63.0 63.0 60.0
63.5 63.6	63.6 63.6 64.0
62.6 62.6 62.6 62.0 63.0	62.6 62.6 62.6 62.0 62.0 62.0 62.0 60.5 60.5 60.5 60.0
62.0 63.0 60.0	62.0 62.0 62.0 62.0 62.0 62.0 60.0 60.0
61.5 61.5 61.5 61.5 61.5 61.5 61.5 61.6 61.6 61.6 61.6 61.7	61.5 61.5 70.00 70
60.5 61.0 60.5	60.0 60.0
50.5 50.5	50.55 50.56 50.56 50.57 50.56 50.57
59.99 50.14 50.17 50.17 50.18 50.18 50.18 50.19	59.99 50.14 50.17 50.18 50.18 50.19
59.4 50.4 50.4 50.4 50.4 50.4 50.4 50.6 50.5 50.6	59.4 50.4
56.3 56.3	56.3 56.1 56.1 56.1 56.2 56.3
52.1	52.1
60.0 60.5 60.5 60.5 60.5 60.5 60.6 60.5 60.6	60.0 60.5
61.8 61.7 61.1 701.0 61.1 701.0 60.5 701.0 700.0	61.8 305.4 25.9 1.00003 50.5 50.6 1.00003 50.5 50.6 1.00003 50.6 50.6 1.00003 50.6 1.00003 50.6 1.00003 50.6 1.00003 50.9 1.00003 50.9 1.00003 50.9 1.00003 50.9 1.00003 50.9 1.00003 50.5 50.6 1.00003 50.5 50.6 1.00003 50.5 50.6 1.00003 50.5 50.6 1.00003 50.5 50.6 1.00003 50.5 50.5 50.6 1.00003 50.5 50.5 50.5 50.6 1.00003 50.5 50.5 50.5 50.6 1.00003 50.5 50.5 50.5 50.6 1.00003 50.5 50.5 50.5 50.5 50.6 1.00003 50.5 50.5 50.5 50.5 50.5 50.5 50.
61.7 61.1 701.0 60.5 701.1 701.5 70.6 70.6 70.6 70.6 70.6 70.6 70.6 70.6	61.7
50.5 50.6	59.5 59.9
50.6 50.6 50.6 50.6 50.0	50.6 59.4 59.4 59.8 50.9
59.4 58.8 59.9 50.9	59.4 58.8 59.9 50.9 50.9 50.9 50.9 50.9 50.9 50.9 50.9 50.9 50.9 50.9 50.9 50.0
58.8 400.4 25.9 1.0000.3 55.9 1.0000.3 55.9 1.0000.3 55.6 1.00000.3 55.6 1.00000.3 55.6 1.00000.3 55.6 1.00000.3 55.6 1.00000.3 55.6 1.00000.3	58.8 400.4 25.9 1.0000.2 55.9 1.0000.2 55.9 1.0000.2 55.6 1.0000.2 55.6 1.0000.2 55.6 1.0000.2 55.6 1.0000.2 55.6 1.0000.2 55.0 1.00000.2 55.0 1.0000.2 55.0 1.0000.2 55.0 1.0000.2 55.0 1.0000.2 55.0
59.9 59.9 50.9	59.9 100.00 25.6 1.0000 4.6.2
64.3 64.3	64.3 64.3 64.3 64.4
53.5 54.7 54.7 55.6 56.7 56.2 56.2 56.2 56.2 56.2 56.2 56.2 56.3	53.3 53.5 54.7 54.7 55.6 1.00007 67.0 67.0 67.0 67.0 68.2 7.00007 68.3 7.00007 7.00007 7.00007 7.00007 7.00007 7.00007 7.00007 7.00007 7.00007 7.00007 7.00007 7.00007 7.00007 7.00007 7.00007 7.00007 7.00007 7.00007 7.00007
53.5 54.7 54.7 55.0 1.000UT 67.0 67.0 67.0 67.0 67.0 7.00UT 68.2 7.00UT 7	53.5 54.7 54.7 55.0 1.00001 67.0 67.0 68.2 762.2 31.5 1.00002 59.2 70.5 70.0 70.0 70.0 70.0 70.0 70.0 70.0
64.7 65.6 65.6 67.0 67.0 68.2 68.2 7.000 68.3 7.000 7.000 7.000 7.000 7.000 7.000 7.000 7.000 7.000 7.000 7.00000 7.0000 7.0000 7.0000 7.0000 7.0000 7.0000 7.00000 7.00000 7.0000 7.0000	64.7 65.8 67.0 67.0 67.0 67.0 67.0 68.2 762.2 762.2 762.2 762.3 762
65.8 261.7 28.7 1.00000000000000000000000000000000000	65.8 2 26.2 31.5 1.00000 26.3 26.3 26.3 26.3 26.3 26.3 26.3 26.3
64.0 262.2 31.5 1.0000.2 66.8 2 240.5 2.6 2.7 240.0 1.0000.2 26.8 2.8 2.8 2.8 2.8 2.8 2.8 2.8 2.8 2.8 2	67.0 762.2 31.5 1.000.2 68.2 7562.7 34.3 1.000.2 762.8 79.5 7.000.2 79.5 7.000.2 79.5 7.000.2 79.5 7.000.2 79.5 7.000.2 79.5 7.000.2 79.5 79.5 79.5 79.5 79.5 79.5 79.5 79.5
68.2 240.5 24.4 1.00002 59.2 24.3 1.00002 59.2 24.3 1.00002 59.2 24.3 1.00002 59.2 25.2 1.00002 59.2 25.2 1.00002 59.2 25.2 1.00002 59.2 25.2 1.00002 59.2 25.2 1.00002 59.2 25.2 1.00002 59.2 25.2 1.00002 59.2 25.2 1.00002 59.2 25.2 1.00002 59.2 25.2 1.00002 59.2 25.2 1.00002 59.2 25.2 1.00002 59.2 25.2 1.00002 59.2 25.2 25.2 1.00002 59.2 25.2 25.2 25.2 25.2 25.2 25.2 25.	68.2 262.7 34.1 1.0000.0 59.2 59.2 70.0 70.0 70.0 70.0 70.0 70.0 70.0 70
00000000000000000000000000000000000000	50.8 720.5 24.1 1.00007 50.2 24.2 1.000007 1.000000 1.000000 1.0000000 1.000000000
	59.5 283.8 22.5 1.00000000000000000000000000000000000
2000 1 2 2 8 8 2 2 6 6 6 6 6 6 6 6 6 6 6 6 6 6	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
	2000 1 18 8 8 8 5 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6
69.8 1.6.1 15.3 1.000	

UPPER ATR DATA

GEODETIC COORDINATES

A TAT	LTITUDE 39	CO.O. FEET		175.032	6 5		6 500 6 71 0	COORDINA
بي .		かいぞ ひとま かいいつ		PROJE SANDS	v a		5	40.043
SCEMETO	10. 001			,			106.	47053 LON
				TABLE 15	Con't			
\$. 60	FP C .tt .t.	6 3 de 1	REL.HUM.	111547	ر د	٥	₹ ► ■	ANDEX
11.11.11			R 13H 3	UB 1C	SOUND	(119N	SPEFU	5 0
٠,	* TELILAR	DIGRIES CENTIUPA		E TE	NOT	SPEE	KNOTS	KEFRACTION
	•	-53.7		•	73.	~	•	0000
6 4 (7) 4 13	2.65	-50.5		¥	570.8	317.0	13.3	1.000072
.5	u)	~		•	7.	\sim		.300.
50.00.	'n	S		Ľ.	71.	~	-	.0000
55.00	5	-58.4		٠,	5	~	ċ	.0000
	;	* * S 5 *		u.	70.	4	•	.0000
65 TC •		~		ċ	6.5	_	•	0000
26 De	-	S		•	, ,	C * y *		0000
75.0.	-	-53.5		÷	ů.	\$ 0.0		0000
сі Сі	•			o.	72.	56.5	•	0000
85 U.	ن	6.		•	7	5 4.5	÷	0000
9000°	•	5			73.	¥.0,	•	0000
95.0.	š	₩.			.33	50.5		0000
JC JC	,	-56.2		÷	73.	7.7		0000
JS LU.	7	V١		<u>-</u> •	73.	7.5		0000
1000	• 7	•		å	74.	K.2	•	. 1000
15.0	:	~		ċ	74.			.0000
61.50	3	-56.€		05.3	574.1	357.7	•	000
ć)	٠ د	~		•	74.	'n	•	. 000.
Jr. 1.	;)	• •		,	74.	S	•	.0000
35.7.	۲.	S.		ċ	75.	Š	•	.000
• () ()	۲.	v		ċ	75.	er	۲.	. 2000
· 5 57	3	~		•	75.	43.6	•	.0000
50.00	š	•		÷	76.	56.4	×.	.0000
55 7.	•	V١		, ,	76.	53.7	~	.0000
(၁၀)	÷	~		, •	75.	50.7	•	.000.
ري. ا	.,	~		٠,	7.7	5.7	٠,	. 000 .
76.35	•	5 0 1		•	7.7	7.25	÷.	0.10.
.0.57	_:	~		•	00 (17.0	•	.0000
٠ ج پور	;	~		o* 1	60 1		•	0000.
. D. 38	٠ ح	-52.5			φ 00	27.	•	0000.
9()•	÷	W)		₹	76.	4.5.1	•	0000.
15 60	ŝ	-53.1		٠,	77.	40.4	•	0000.
<u>ر</u> ن ، ،		S		7	7.7	\$ 2.5	ô	. 000 ·
	۲.	S		ľ	77.	2.35	ċ	. <u>೧</u> ೨೯೧
ات بر	Š	₽		۲.	78.	2.44	•	0000
• • • • • • • • • • • • • • • • • • • •	٠ د	-52.3		-	43.	\$ · 0 ?		0000
• uú :32	•	٠.		c*	46.	\sim	x x	Lugu
.503.	•	2.15-		29.0	٠ ن	6.0%	•	0000
: Si	;	-57.5		~	٠ <u>.</u>	~1	~	ูก อ ด

STATION ALTITUDE 3969-50 FEET WSL 1. APR. 84 0525 MMS MST ASCENSION NO. 127

UPPFR AIR DATA
1750424247
WHITE SANDS

GEODETIC COORDINATES 32.4U043 LAT DEG 106.37933 LON DEG

TABLE 15 Con't

LOME 14	PRESSURE	7 E M P	44.	REL-HUM.	, ,	E E D	0 6713	4	INGER
MSL F F1	MILLIBARS	DEGRES	Z •£	E 1 1	METER	KNOTS	DEGREES(TN)	KNOTS	REFRACTION
825000	٢.1	Ċ			,	81.	25.	14.8	00
848,0.0	.35	•			ç	81.	č.		900
845 0.0	7,	•			34.5	580.9	338.3	14.6	1.000000
0°C\553	76.	٠			,	å Ö	46.		000
8.55 m.n.	21.	-51.				e Ca	54.		0000
3¢7 0°6	-12	-50.3			٠.		•		2000
465.3.0		5.67-			د	82.	•		0000
376 74.9	rs.	-48.0			-	x 3.	10.4		C
875 7.0	19.	-48.1			ċ	. 78	-		8
0.038	19.	-47.1				. 4 .		0	.000
845 %	٠٥٢	7.7.			ċ	×5.	4	_	0
0° ທີ່ ປັດ ໔	18.	-47.1			•	85.	C,	-	000
0.500	• • •	7.07-				96.	V.	•	$^{\circ}$
900000	17.	-40.4			۲.	86.	Ξ,	•	\mathbf{c}
9.0000	17.				ţ	9.7.	œ,	-	000
916.0.6	16.	1.54-				87.	÷	~	0000
915.0.0	16.	-45.4			ď	88.	₩,	~	0000
0 *Ω00?6	10.	7.53-				88		~	00
S.S. 25.6	15.					88	5.7	23.7	000
0.0000	15.	-44.5			۳,	680	~	ø	00
ტ ქვეს• ე	15.				٠.	٠ 0 ۲	34.	0	2
0.00000	14.	-43.7			۲,	90.	٤.	•	0000
9.45 F.2.0	14.	-43.6				00	•	•	1 000
6.00.086	3 4.	-45.5			•	ე	•	\sim	0000
9.55 Jr. 0	13.	-43.5			c*	60.	٠,	c,	3
0.07.326	13.	-43.4				93.	÷	0	000
965 C1 • C		-45.2			•	90.	,	0	$\boldsymbol{\smile}$
27.5.7.6	16.	-43.3			o.	9).	: `	0	GOO
977.00.0	14.	-43.6			Ç.	90.	<u>.</u> ب	18.0	
0°03086	• 7	-43.6				5	•	~	1.0000-1
C*21.28.2	1	-43.1			•	٠ ري	12.	~	2
0.05 Jko	11.	-43.1				000	304.4	22.5	0
0.0 545	11.	0.54-			•	63.	40	•	0000
1000 0.00	11.	-45.0			•		.76	œ.	0
1005.040	-	-42.7			•	591.1			1.000J
1117 30.5	5	6.57-			•	٥.			5
101530.0	10.	-42.3			•	501.3			C.
10.26.19.0	16.	0.44			5 ° 5 €	591.3			00
6-18 M-18	-1	7.7.7-			15.2	501.4			3

STATION ALTITUDE 1959-60 FEET FOL 1. APH. 0. 05.5 HAS MST ASCENSION VO. 207

MANDATORY LEVELS 10200207 WHITE SANDS

GEORETIC COOMBINATES 32.4U043 LAT REG 1U6.37033 LON REG

TABLE 16

DATA V SPEED	201	12.4	8.9	9.5	•	-	~	12.0	S	S	_	0	\sim	•	S	~	\sim	-	~	23.2	\sim	m)	-	7.6	8.7	8.6	$\boldsymbol{\omega}$	20.3	
DIRECTION	ביי ביי ביי	21.9	10.3	332.0	256.4	574.9	2 ° 13	278.5	281.4	287.1	263.5	274.1	274.5	274.6	7.16	288.9	291.4	302.6	361.0	287.6	264.7	310.5	58.4	154.8	1.5.1	0.44.	10.9	354.1	
PEL.HUM. Percfnt		19.	•		v	~	90	10.	~	-		•																	
RATURE Dewpoint	L. N. LGKAUE	-10.7	-11.	-12.0	7.6-	~	0	-22.7	₩.	\sim	-40.3	•																	
AIR	0 : 0 × E E Ø		11.0	8.1	4.3	1.0	7.2-	-B - 7	- 14.9	- 19.5	-26.1	- 53 - 3	- 42 • 3	-52.3	-62.4	- 62.4	6.53-	- 65.8	- 65.3	- 64 . 3	- 00-1	- 58.6	- 58.2	•	-52.5	1.11.4	- 48 . 3	C • 74 -	Z * 2 * -
UFUTCUTAL	- - - - -	4 3 € 4	6522.	€ 5.7 ª •	10153.	12098.	14191.	16425.	18527.	21412.	24247	27279	7.802.	34817	* 1444°	42131.	42.358.	46715.	13361.	:27795	40498.	63555.	177721	,22.72.	701.5.	21967.	96763	936.9	101098.
	MILLIENTS	85)•0	800.0	72.3.9	703.0	657.3	0.004	553.0	0°U04	457.9	6.004	350.0	300.0	25? • 0	203.0	17.00	153.0	1,5,0	10.0	8.1.9	0.07	0.00	ວູິເ		ე• ⊬ §	U ?	G* 37	10.0	13.0

AT LEAST OVE ASSUMED RELATIVE HUMINITY VALUE WAS USED IN THE INTERPOLATION.

·9-84

T

 \bigcirc